

Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating

120VAC	60 Hz	0.35 Amps
277VAC	60 Hz	0.15 Amps



- PAR-36 Sealed Beam Lamps, 6-Volt – 25-Watt



- Refillable Lead Acid Battery
- 32°–105°F Operating Range
- 6-Volt Operation
- 8–12 Year Operating Life



- Rugged 20-Gauge Steel Housing
- Top End Battery Access
- Keyhole Mount Standard or Order Shelf No. 23
- Beige Powder-Coat Finish Standard
- Test Switch
- Red (Power On) & Green (Trickle Charge) LED Indicators
- UL Listed

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2AR6L40†	25	120	90	60	45	36	30	26	23	(1) L640
H2AR6L40†	20	120	90	60	45	36	30	26	23	(1) L640

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	AR	6	L	40	-P2
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (L – Lead Acid)	Battery Amp/Hour	Options



Shown in Standard Beige Finish

Dimensions

AR

Height: 12.7"
Width: 11.9"
Depth: 4.9"

Options

Add Suffix to Catalog Number

- GY Industrial Grey Finish
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- TD Time Delay – Adjusts 1–60 min.
- ** Special Lamp Wattage (See page 50)

The AR Series is equipped with a refillable lead acid battery, providing 8 to 12 years of service in ambient temperatures ranging from 32° to 105°F.

