



Standard Heads

Shown in Optional White Finish



Round Heads

Shown in Standard Designer Off-White Finish (Round Heads Only)

Dimensions

**STANDARD HEADS**

Height: 13.8"  
Width: 10.3"  
Depth: 3.5"

**ROUND HEADS**

Height: 15.4"  
Width: 10.3"  
Depth: 3.5"

Maximizing remote head performance in a low-cost, traditionally styled fixture, the CL Series is capable of powering up to 100 watts in remote lamp loads.

Options

Add Suffix to Catalog Number

- BC** Beige & Cocoa Two-Tone Finish
- BG** Beige Finish
- BLK** Black Finish
- P2** Cord & Plug for 120VAC Input
- TD\*** Time Delay – Adjusts 1–60 min.
- W** White Finish
- \*\*** Special Lamp Wattage (See page 50)



**\*(Not available on 2CL6536 and 2CL12515)**

Series Features


- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Fused AC Input & DC Output Circuit Protection
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.35 Amps  
277VAC 60 Hz 0.15 Amps



- HIT Lamps
  - PAR-36 Sealed Beams
- STD Lamp: See Unit Information



- Sealed Lead Calcium Battery
- 6- or 12-Volt Operation
- Maintenance-Free



- 20-Gauge Steel Housing
- Rectangular Polycarbonate Head Units: Standard Beige Powder-Coat Finish
- Round Steel Head Units: Standard Off-White Powder-Coat Finish
- Keyhole Mount
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #38236

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2CL6S5	6	12	9	6	–	–	–	–	–	(1) S65
2CL6S8	6	18	14	9	7	–	–	–	–	(1) S68
2CL6S10	6	32	24	16	12	10	8	7	6	(1) S610SL
2CL6S16	6	45	36	20	15	12	10	9	8	(2) S68
2CL6S20	6	64	50	32	24	19	16	14	12	(2) S610SL
2CL6S36	6	100	75	50	38	30	25	21	18	(1) S636
2CL12S7	7	36	27	18	14	11	9	8	7	(2) S68
2CL12S10	7	60	45	30	23	18	15	13	11	(2) S610SL
2CL12S15	7	100	75	50	38	30	25	21	18	(1) S1215

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

Ordering Information

<b>H</b>	<b>2</b>	<b>CL</b>	<b>12</b>	<b>S</b>	<b>7</b>	<b>-12</b>
Halogen Lamp Prefix	Lamp Heads on Unit	Series	DC Battery Voltage	Battery Type (S – Sealed)	Battery Amp/Hour	Options

For Rectangular Heads with Special HIT Wattage Lamps, add Lamp Wattage as Suffix Number. For Round Heads with Special HIT Wattage Lamps, add Suffix "R" and Lamp Wattage. For Round Heads with Tungsten Sealed Beam Lamps, add Suffix "S" and Lamp Wattage. For Round Halogen Sealed Beam Lamps, add Prefix "H" and Lamp Wattage. **Note:** Total Lamp Wattage cannot exceed 1.5 HR. Unit Capacity.