



# (Remote Capable) New York City Approved 8" LED Exit/Emergency Combo

### GENERAL DESCRIPTION

The value series LED exit provides high quality extruded aluminum construction, at low operating costs. Illumination is provided utilizing the highest quality LEDS (AllnGaP) for precise evenly distributed trouble-free operation. Integral Heads, if selected, have 10 Bi-Pin halogen lamps in a Metalized reflector assembly. The lens is tempered glass.

### HOUSING

Rugged, durable extruded aluminum construction Exit, offers superb corrosion resistance. Factory attached and pre-wired emergency lighting is constructed of heavy gauge galvanized steel

### MOUNTING

All units are shipped with parts necessary to mount sign (back wall mount only). Adapts to standard 3 1/2" octagonal or 4" square junction box.

# FACE DESIGN

Provides 8" letters with 1" stroke. Stencils have easy to use direction marking knockouts. Housing Back has knockouts to accomodate Wall Mounting .

### ILLUMINATION

High Output AllnGap LEDS with rated lamp life of 10 years. Exit sign draws less than 3 Watts. Remote capacity based on total wattage specified.

### **ELECTRONICS**

Input is dual volt standard 120/277 60Hz. Union features solid state design with low voltage disconnect, AC lockout, brown out protection, and AC indicator LED with test switch. Provides Minimum of 90 minutes of illumination upon loss of power. Battery is maintenance free Sealed Lead Calcium.

## CODE COMPLIANCE


UL 924 listed NFPA NEC and OSHA illumination standard.


### WARRANT

5 years on housing and electronics with a 5 year pro rated warranty on battery.



**DIMENSIONS** 





\*Note: To determine Maximum Remote Wattage, Subtract total integral lamp Watts from total DC Unit Wattage.

Example: 50 Watts (Total DC Wattage)minus Aprox.20 Watts (2X10 Watt integral Lamps) Equals 30 Watts Maximum available for remote lamps

