



New York NY-LX Series - 6 Volt

6 Volt Emergency Operation Light




PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____



NY-LX-18-2

NY-LX-27-3 & NY-LX-50-3



NY-LX-18-2

NY-LX-27-3 & NY-LX-50-3

PRODUCT DESCRIPTION

The ny-lx Series New York Emergency Lights are designed for efficiency and ease of installation. Their rugged design meets New York City standards and provides dependable operation. These units are completely self contained and fully automatic.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Rugged, heavy duty design • 20 gauge steel housing and faceplate • Lamp heads made from high impact resistant thermoplastic.

ELECTRICAL

Dual voltage 120/277VAC • Solid state charging and switching • Brownout protection • Battery Low Voltage disconnect • Overload and short circuit protection • AC power \ indicator and test switch.

BATTERY

Maintenance-free 6V sealed lead calcium battery will operate rated load for a minimum of 90 minutes in the event of a power outage.

LAMPS

Supplied with 6V, 9W, Tungsten wedge base type lamps • Two or three heads units.

CODE COMPLIANCE

UL Listed • NFPA 101 Life Safety Code compliant • NEC and OSHA compliant • City of New York Approved • Calendar No. 46932.

WARRANTY

Five Year total customer satisfaction warranty on exit, including lamps.


INSTALLATION

MOUNTING

Keyhole slots and J-Box mounting holes provided for simplified wall mounting.

PHOTOMETRICS

6V, 9W Tungsten Wedge Base Lamp (ANSI 908), Round Head



NY-LX-6-18 ENGINEERING DATA

INPUT VOLTAGE	MAX. AMPS	MAX. WATTS	STAND-BY WATTS
120	0.062	6.8	1.5
277	0.031	7.6	1.5

NY-LX-6-27 ENGINEERING DATA

INPUT VOLTAGE	MAX. AMPS	MAX. WATTS	STAND-BY WATTS
120	0.062	6.9	1.3
277	0.034	8.8	1.3

BATTERY DATA

TYPE BATTERY	VOLTAGE	SHELF LIFE ¹	EXPECTED LIFE ¹	TEMP. RANGE ²
Lead Calcium (NNY618)	6V, 7Ah	15 months	5-8 years	40°F-95°F
Lead Calcium (NNY627)	6V, 10Ah	15 months	5-8 years	40°F-95°F

• Lead Calcium battery warranted for one full year with additional 4 years pro-rated warranty

• Recharges in 24 hours or less ¹ At 77°F

² To obtain rated life and capacity

ORDERING INFORMATION

MODEL	DESCRIPTION
NY-LX-18-2	6 Volt, 18 Watt Indoor Emergency Unit, Two 9 Watt Heads
NY-LX-27-3	6 Volt, 27 Watt Indoor Emergency Unit, Three 9 Watt Heads
NY-LX-50-3	12 Volt, 50 Watt Indoor Emergency Unit, Three 12 Watt Heads

Ordering Example: NY-LX-27-3



New York NY-LX Series - 12 Volt

12 Volt Emergency Operation Light




PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____



NY-LX-18-2

NY-LX-27-3 & NY-LX-50-3



NY-LX-18-2

NY-LX-27-3 & NY-LX-50-3

PRODUCT DESCRIPTION

The NY-LX Series New York Emergency Lights are designed for efficiency and ease of installation. Their rugged design meets New York City standards and provides dependable operation. These units are completely self contained and fully automatic.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Rugged, heavy duty design • 20 gauge steel housing and faceplate • Lamp heads made from high impact resistant thermoplastic.

ELECTRICAL

Dual voltage 120/277VAC • Solid state charging and switching • Brownout protection • Battery Low Voltage disconnect • Overload and short circuit protection • AC power indicator and test switch.

BATTERY

Two maintenance-free 6V sealed lead calcium batterie connected in series to deliver 50 watts of rated capacity Will operate the unit's three heads plus an additional 14 watts of remote capacity for a minimum of 90 minutes in the event of a power outage.

LAMPS

Supplied with 12V, 12W, Tungsten wedge base type lamps • Two or three heads units.

CODE COMPLIANCE

UL Listed • NFPA 101 Life Safety Code compliant • NEC and OSHA compliant • City of New York Approved • Calendar No. 46932.

WARRANTY

Five Year total customer satisfaction warranty on exit, including lamps.


INSTALLATION

MOUNTING

Keyhole slots and J-Box mounting holes provided for simplified wall mounting.

PHOTOMETRICS

6V, 9W Tungsten Wedge Base Lamp (ANSI 908), Round Head



NY-LX-12-50 ENGINEERING DATA

INPUT VOLTS	MAX. AMPS	MAX. WATTS	STAND-BY WATTS
120	0.15	15.7	2.5
277	0.07	16.6	2.2

BATTERY DATA

BATTERY TYPE	VOLTAGE	SHELF LIFE ¹	EXPECTED LIFE ¹	TEMP. RANGE ²
Lead Calcium	6V, 10Ah (2)	15 months	5-8 years	40°F-95°F

• Lead Calcium battery warranted for one full year with additional 4 years pro-rated warranty

• Recharges in 24 hours or less ¹ At 77°F

² To obtain rated life and capacity

ORDERING INFORMATION

MODEL	DESCRIPTION
NY-LX-18-2	6 Volt, 18 Watt Indoor Emergency Unit, Two 9 Watt Heads
NY-LX-27-3	6 Volt, 27 Watt Indoor Emergency Unit, Three 9 Watt Heads
NY-LX-50-3	12 Volt, 50 Watt Indoor Emergency Unit, Three 12 Watt Heads

Ordering Example: NY-LX-27-3