




E-Star Series - SX

SX-AC ONLY Steel LED Exit



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____



PRODUCT DESCRIPTION

With appealing designs and dependable performance, the E-Star Series of LED exit signs will accommodate virtually any application. Designed for ease of installation, this versatile exit sign features an all-in-one design that uses the same compact housing for both ac and Battery-Backup models. The led light source provides years of maintenance-free illumination at a minimal cost.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Rugged, heavy duty 20-gauge die-formed steel construction – Universal mounting pattern knockouts in backplate for back mounting – Second faceplate included for double face applications – 6” letters with 3/4” stroke width – Chevron directional indicator knockouts – Red or green letters – Corrosion-resistant polyester powder coat paint – White or black finish.

ELECTRICAL

Dual voltage 120/277VAC.

LAMPS

Long life, energy saving LED lamps – LEDs are connected in a series/parallel configuration such that the unlikely failure of one LED will affect no more than one other LED – Red or green LED/letters – Red signs consume less than 5 watts – Green signs consume less than 2 watts.

CODE COMPLIANCE

UL Listed – NFPA 101 Life Safety Code compliant – NEC and OSHA compliant. Meets the State of Minnesota energy efficiency requirements –

WARRANTY

5-year warranty. Product specifications subject to change without notice.

INSTALLATION

MOUNTING

May be top, end or back mounted – All signs include canopy and mounting hardware for easy top or end mount installation – Backplate includes universal mounting pattern knockouts for simple back mounting.

ACCESSORIES

ACCESSORY	DESCRIPTION
WG2	Wire Guard
PK12	Pendant Kit - 12"
VRS	Vandal Resistant Shield

Add suffix to model

ORDERING INFORMATION

MODEL	FACES COLOR CODE	OPTIONS	
SX = AC Only	1 =Single with Canopy	WWR = Red Letters, White Housing	SD = Self-Diagnostics
PSX = Battery Backup	2 =Double with Canopy	WWG = Green Letters, White Housing	DLC = Dual Circuit
	1/2C = Universal (Double Face	BBR = Red Letters, Black Housing	SL = Special Lettering
	with Canopy & Back Plate)	BBG = Green Letters, Black Housing	TP = Tamperproof Screws
		(Call for other combinations)	FL = Flasher
			BZ = Buzzer
			ERT = Extended Run Time

Ordering Example: PSX-1-WWR-VRS




E-Star Series - PSX

PSX-BATTERY BACK-UP Steel LED Exit



PROJECT: _____
 FIXTURE TYPE: _____
 LOCATION: _____
 CONTACT/PHONE: _____



PRODUCT DESCRIPTION

With appealing designs and dependable performance, the E-Star Series of LED exit signs will accommodate virtually any application. Designed for ease of installation, this versatile exit sign features an all-in-one design that uses the same compact housing for both ac and Battery-Backup models. The led light source provides years of maintenance-free illumination at a minimal cost.

PRODUCT SPECIFICATIONS

CONSTRUCTION

Rugged, heavy duty 20-gauge die-formed steel construction – Universal mounting pattern knockouts in backplate for back mounting – Second faceplate included for double face applications – 6” letters with 3/4” stroke width – Chevron directional indicator knockouts – Red or green letters – Corrosion-resistant polyester powder coat paint – White or black finish.

ELECTRICAL

Dual voltage 120/277VAC. – Solid state charging and switching – Brownout protection – Battery low voltage disconnect – Overload and short circuit protection – AC power indicator and test switch.

LAMPS

Long life, energy saving LED lamps – LEDs are connected in a series/parallel configuration such that the unlikely failure of one LED will affect no more than one other LED – Red or green LED/letters – Red signs consume less than 5 watts – Green signs consume less than 2 watts.

BATTERY

Long life, maintenance-free, high performance nickel cadmium – Designed to operate over a wider range of temperature conditions (32°F-100°F recommended operating range) – Battery will operate sign for a minimum of 90 minutes in the event of a power outage.

CODE COMPLIANCE

UL Listed – NFPA 101 Life Safety Code compliant – NEC and OSHA compliant. Meets the State of Minnesota energy efficiency requirements

WARRANTY

5-year warranty. Product specifications subject to change without notice.

INSTALLATION

MOUNTING

May be top, end or back mounted – All signs include canopy and mounting hardware for easy top or end mount installation – Backplate includes universal mounting pattern knockouts for simple back mounting.

ENGINEERING DATA

	INPUT VOLTS	MAX. AMPS	MAX. WATTS	STANDBY WATTS*
Red LED	120	0.05	4.7	4.5
Red LED	277	0.02	4.9	4.7
Green LED	120	0.02	1.9	2.6
Green LED	277	0.01	1.9	2.7

* Fully charged battery.

ACCESSORIES

ACCESSORY	DESCRIPTION
WG2	Wire Guard
PK12	Pendant Kit - 12"
VRS	Vandal Resistant Shield

Add suffix to model

ORDERING INFORMATION

MODEL	FACES COLOR CODE	OPTIONS	
SX = AC Only	1 =Single with Canopy	WWR = Red Letters, White Housing	SD = Self-Diagnostics
PSX = Battery Backup	2 =Double with Canopy	WWG = Green Letters, White Housing	DLC = Dual Circuit
	1/2C = Universal (Double Face with Canopy & Back Plate)	BBR = Red Letters, Black Housing	SL = Special Lettering
		BBG = Green Letters, Black Housing	TP = Tamperproof Screws
		(Call for other combinations)	FL = Flasher
			BZ = Buzzer
			ERT = Extended Run Time

Ordering Example: PSX-1-WWR-VRS