

JOB NAME:

TYPE NO.:

CATALOG NO.:



High-Lites

AG1 Series Steel Recessed Gimbal Emergency Lighting Units

ORDERING INFORMATION

Catalog Number: Example: AG1B220

MODEL NUMBER

Lead Calcium Models
AG1 - 6V, 12W
Nickel Cadmium Models
AGN1 - 6V, 10.8W

HOUSING COLOR

Blank - White (Std.)
B - Black
SP - Special Color

OPTIONS

see below

OPTIONS (1)(2)

220	220V, 50Hz input
------------	------------------

(1) Other options available.

(2) Some options may impact UL listing.



SPECIFICATIONS

Construction	Housing: Heavy duty steel construction. Trim ring is finished in baked-on powder paint providing scratch and corrosion resistance. The gimbal ring allows full adjustment of the unit lighting head.
Installation	A plaster ring is supplied with provisions for mounting bars (supplied by installer). Wiring: A junction box is included with the plaster ring assembly for making AC connections. The gimbal/lamp assembly is provided with a plug-in connector.
Illumination	Emergency illumination in AG1 and AGN1 models is provided by 6V, 7.2W (10) Par 36 incandescent sealed beam lamp. Prismatic lenses provide bright, even, glare-free operation in a wide pattern across the path of egress.
Electronics	<ul style="list-style-type: none"> Dual input 120/277VAC, 60 Hz AC Lockout protection AC-On indicator light and test switch Low voltage battery disconnect Automatic charger and transfer circuit Automatic brownout protection
Power Consumption	Input Power: 15W (maximum charge), 3W ready state.
Battery	Choice of 6V, lead calcium or nickel cadmium sealed maintenance free battery. Optimum operating temperature range: 68°F to 86°F (20°C to 30°C). Provides a minimum of 90 minutes of full output emergency illumination.
Code Compliance	Listed to UL924. Meets NFPA Life Safety Code 101. Complies with NEC and OSHA.
Warranty	Limited 3-year warranty. 3-year lead calcium or 5-year nickel cadmium prorate battery warranty.

Specifications are subject to change without notice. Consult website for latest version of this spec sheet. Crescent/Stonco • 200 Franklin Square Drive • Somerset, NJ 08873 • 800-334-2212 • www.crescentlighting.com


Crescent is a Philips company



PRODUCT FEATURES

- Very low profile design
- Rugged steel housing and trim ring in white finish
- Mounting plate allows fast, easy installation in suspended T-grid or drywall ceilings
- Adjustable, glare-free lighting head
- Choice of maintenance-free lead calcium or long life nickel cadmium battery models
- 90 minutes of emergency illumination
- Universal 120/277VAC input
- Fully automatic battery charger and transfer circuit
- Automatic low voltage battery disconnect
- Automatic brownout protection
- AC lockout feature reduces installation time
- Momentary test switch and AC ready indicator
- UL operating range 68°F to 86°F (20°C to 30°C)
- Meets NFPA Life Safety Code 101, NEC and OSHA
- UL924 listed

DIMENSIONS



NOTE: Dimensions and specifications subject to change without notice. Form 1117A 04/12

© 2006 Philips group

