



CLSC Series

Chicago LED Steel Combo

FEATURES

Description

The CLSC Series is a Chicago Approved combination exit/emergency light that uses 2 each 5.3W adjustable white LED lamp-heads to provide emergency lighting for the required 120 minutes. The CLSC can be wall mounted by use of a back-plate, which includes a universal knock-out pattern or ceiling/end mount by use of a supplied canopy. Available with 6" tall, 3/4" stroke STAIRS or EXIT red lettered panels in single or double-face. Housing made of durable 20 gauge steel with panels made of glass.

Application

The CLSC Series can be applied inside buildings for general EXIT or STAIRS panel illumination with directional arrow indication, and stairwells that are susceptible to moisture.

The series also includes a No Panel option(-NP for standard model and -NPRC for remote capacity model) which does not include the glass panels for single or double-face. The individual glass panels need to be selected and ordered separately.

Compliances

City of Chicago
 UL924 Damp Location Listed
 NFPA 101
 OSHA

Warranty

5 year full unit warranty

Features

- Universal 120-277VAC input, 60Hz.
- Includes 6VDC sealed lead acid battery
- Full re-charge within 24 hours
- Includes LVD(low voltage disconnect) to protect the battery from deep discharge
- Includes AC-On LED indicator and Push-to-Test switch
- Remote Capacity option
- UL924 Damp Location Listed, 20°C to 50°C

Catalog Number	
Comments	Type



ORDERING GUIDE

CLSC

Model	# of Faces	Letter Color	Housing Color	Options	Panel Code
	S Single D Double	R Red	W White	RC Remote Capacity ² Blank No Remote Capacity	Single Face Models 3 "EXIT" (no arrows) 6 "EXIT" (right arrow) 9 "EXIT" (left arrow) 12 "EXIT" (double arrow) 2 "STAIRS" (no arrows) 5 "STAIRS" (right arrow) 8 "STAIRS" (left arrow) 11 "STAIRS" (double arrow) Double Face Models 18 "EXIT" (no arrows) 21 "EXIT" (right / left arrow) 24 "EXIT" (double arrow) 17 "STAIRS" (no arrows) 20 "STAIRS" (right / left arrow) 23 "STAIRS" (double arrow)

1: The CLSC can be ordered fully configured as above, or by stocked model on next page.
 2: Remote Capacity model has 10 watts remote capacity to run CRH (Indoor or Outdoor remote heads for Chicago)

STOCKED OPTIONS

Stocked Model Options

Model	
CLSCSRW-3	Steel Combination Exit/Unit, No Arrows (CP#-ENA)
CLSCSRW-NP	Steel Combination Exit/Unit, No Panel Included
CLSCSRW-NPRC	Steel Combination Exit/Unit, No Panel Included

Stocked Panel Options

Catalog	Descriptions
CP3-ENA	Exit No Arrow
CP12-EDA	Exit Double Arrow
CP6-ERA	ExitRight Arrow
CP9-ELA	Exit Left Arrow
CP2-SNA	Stairs No Arrow
CP11-SDA	Stairs Double Arrow
CP5-SRA	Stairs Right Arrow
CP8-SLA	Stairs Left Arrow



CLSCSRW-NP



CP3-ENA



CP2-SNA

Notes:

1. Order the -NP or -NPRC option for **single or double-face** and select the required panels separately.
2. When ordering double-face with -NP or -NPRC, ensure 2 panels are selected.
3. For -NP or -NPRC option in double-face with directional arrow, ensure a left and right arrow is selected.

Example: Order CLSCSRW-NP with CP6-ERA and CP9-ERA to make a double-face with both arrows pointing in one direction.

DIMENSIONS

