

NX



### Dimensions

NX  
 Height: 8.2"  
 Width: 12.6"  
 Depth: 1.0"  
 (Single Face)  
 Depth: 2.1"  
 (Double Face)

### Options Add Suffix to Catalog Number

-AF Aluminum Frame  
 -IF Institutional Frame  
 -RM Recessed Mount

### Accessories Order Separately

63 Wire Guard (for Single-Face Back Mount Only)  
 P12NXW 12" Pendant Kit, White  
 P12NXB 12" Pendant Kit, Black  
 VDS Vandal-Deterrent Shield (for Single-Face Back Mount NX Only)



### Series Features



• Requires No Electrical Supply



- Internally Illuminated Glass Tubes Coated with Zinc Phosphor and Tritium Gas
- Initial Brightness
  - 0.15 Foot Lamberts (10 Years)
  - 0.18 Foot Lamberts (15 Years)
  - 0.25 Foot Lamberts (20 Years)
- End-of-Life Brightness Exceeds Minimum Code Requirement of .06 Foot Lamberts



• Requires No Battery Supply



• 10-, 15- or 20-Year Illumination



- No Internal or External Wiring Required
- Completely Sealed
- Explosion Proof
- Waterproof
- Corrosion, Mold and Vapor Proof
- Operating Range: -60°–180°F
- High Impact, ABS Fire-Retardant Case
- LEXAN® Cover
- Ceiling, End or Back Mount
- Universal Chevron Configuration
- Mist White Finish
- Complies with NFPA Life Safety Code, NRC, OSHA and Council of American Building Officials
- UL Listed

### Ordering Information

1	NX	10	W	W	-RM
# Faces	Series	Sign Life	Stencil Color	Housing Color	Options
1		10 Years	Red	White*	Factory
2		15 Years	Green	Black	Options
		20 Years	Black	Grey	

\*Standard