



*Decorative Style Equipment
6 Volt
Maintenance-Free
Lead Calcium Battery*

Black Gimbal Available



application Classic high-hat style unit with gimbal mounted lamp, fully recesses into ceiling with only the lens and trim visible. Ideal for low ceilings and blends inconspicuously with existing recessed lighting schemes.

features

- **CONSTRUCTION:** All components are contained in drawn steel box. Standard finish of trim is white plastic. Optional metal trim has white finish.
- **MOUNTING:** Recess mounts into ceiling. Mounting bars supplied by others. Series 605P1 is UL Listed for use in insulated ceilings.
- **ELECTRONICS:**
 - Automatic, temperature compensated, pulse type charger
 - High capacity, automatic, dust tight instantaneous transfer relay
 - Low voltage disconnect prevents overdischarge of battery. Automatic brownout protection is provided
 - Labor saving AC line latch prevents battery discharge during installation to a non-energized circuit.
- **CONTROLS:**
 - Red charge monitor LED indicates state of charge of the battery.
 - Momentary test switch allows for quick operational check of entire system.
- **POWER REQUIREMENTS:**
120/277 Volt AC

battery

6 volt, long life, maintenance-free sealed lead calcium.

lamp

Furnished with an 8 watt high intensity halogen lamp with a horizontal rotation of 358° and vertical angle adjustable to 42°. For isofootcandle distribution see page 62-66.

options

(Add Suffix to Model No.) Suffix
Black Housing & Gimbal-B

ordering format

605P1-M	/LH5
Series	Lamp

unit selection chart

Volts	Model No.	Capacity in Watts to 87 1/2 % of Nominal Battery Voltage		Standard Lamps		
		1 1/2 Hrs.	2 Hrs.	Watts/ Heads	Type	Lamp Rplc. No.
6	605P1/LH5	8	—	8	Halogen	580.0013
6	605P1-M/LH5	8	—	8	Halogen	580.0013

Note: -M Signifies Metal Trim

dimensions

Dimensions are approximate and subject to change.

