



NB Series

6 VOLT MODELS 10 - 26 WATTS

MODEL	DIMENSIONS
NB-1 NB-2 10 ³ 1⁄4"H	2 ³¹ / ₄ °"D x 12 ¹¹ / ₄ "W

Application

High-Lites NB Series is designed for commercial, industrial and educational facilities which require an attractive high performance emergency light that blends in with any decor.

Standard Features

- Die-formed heavy gauge steel cabinet.
- Dual 120 or 277 VAC input, field selectable.
- 1-1/2 hours of light to an end battery voltage of 87-1/2% of nominal voltage.
- 100% solid-state switching circuit.
- Solid-state line-latched low voltage disconnect circuit provides DC load disconnect protection to guard against battery deep discharge.
- Solid-state short circuit and overload protection on DC output.
- · Momentary test switch.
- AC ready light.
- · Fully adjustable lighting heads.
- AC lockout feature reduces installation time.

Batteries

Provided with each High-Lites Emergency Light is a long-life Lead Calcium maintenance free battery that will provide many years of dependable service. Optional Pure Lead and Nickel Cadmium batteries are available. Consult factory.

Lamps And Heads

High intensity incandescent lamps maximize light through a specially designed lens to provide glare free light distribution. Lighting heads are fully adjustable.

Options

Add	Description		
-V*	Voltmeter		
-A*	Ammeter		
-LC	3 Conductor Cord & Plug (120 VAC)		
-220	220-50Hz VAC Input		
-SX	Self-Diagnostic Circuit		

^{*} Provision for one meter only

Unit Selection Chart

Volts	Capa	city in Watts to 87	Std. Lamp		
	1-1/2 HRS.	2 HRS.	3 HRS.	4 HRS.	,
6	10	-	_	-	5 watts
6	16	11	9	6	incandescent
6	26	20	15	12	(-25) (each head)
	Volts 6 6 6	1-½ HRS. 6 10 6 16	1-½ HRS. 2 HRS. 6 10 — 6 16 11	1-½ HRS. 2 HRS. 3 HRS. 6 10 – – 6 16 11 9	1-½ HRS. 2 HRS. 3 HRS. 4 HRS. 6 10 - - - - 6 16 11 9 6