TYPES OF FIRE EXTINGUISHERS & THEIR USES							
Type of Agent	Class	Sample Applications					
ABC Dry Chemical	ABC	Offices, Retail Stores, and Warehouses					
BC Dry Chemical	BC	Paint Storage, Paint Booths					
Clean Agent	ABC	Server Rooms					
Class K Wet Chemical	K	Restaurant & Commercial Kitchens					
Water	A	Offices, Assembly					
Water Mist	AC	Computer Labs					
Foam	ВС	Flammable Liquid Storage, Dip Tanks					
CO <sub>2</sub>	ВС	Welding Shops					
Class D Dry Powder	D	Machine Shops					



466227K

## PRO LINE™ MULTI-PURPOSE FIRE EXTINGUISHERS

Featuring metal valves and aluminum or steel cylinders, these extinguishers are designed to meet most commercial and industrial applications. Their seamless cylinders also come with chip-resistant paint, and their handles and levers are made of pressed heavy-gauge metal for added strength. Checking the pressure is fast and easy, too, thanks to at-a-glance gauges. These units use a non-toxic monoammonium phosphate agent that effectively fights Class A, B, and C fires.

Part No	Description	Net Agent Wt (Avg)	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N
466227K	2.5 lb ABC w/ Wall Hook	2.6 lb	3.9 lb	14¼"	55/16"	31/4"	1A:10B:C	466401K
46622701K	2.5 lb ABC w/ Metal Vehicle Bracket	2.6 lb	3.9 lb	141/4"	55/16"	31/4"	1A:10B:C	466401K
466112K	5 lb ABC w/ Wall Hook	5.5 lb	9 lb	165/16"	713/16"	4½"	3A:40B:C	466400K
46611201K	5 lb ABC w/ Metal Vehicle Bracket	5.5 lb	9 lb	165/16"	713/16"	4½"	3A:40B:C	466400K
466204K	10 lb ABC w/ Wall Hook	10 lb	16 lb	19½"	83/16"	51/4"	4A:60B:C	366242K
466206K	20 lb ABC w/ Wall Hook	18 lb	30 lb	21%"	85/16"	7"	6A:80B:C	292474K











## PRO PLUS™ MULTI-PURPOSE FIRE EXTINGUISHERS

Full featured, covering industrial and commercial fire protection needs, these extinguishers come fitted with a pressure gauge (for at-a-glance status) as well as a durable metal valve, handle, and lever. An impact-resistant steel cylinder is also standard for each model. Suitable for Class A, B, and C fires.

Part No	Description	Net Agent Wt (Avg)	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N
468000K	2.5 lb ABC w/ Vehicle Bracket	2.6 lb	4.38 lb	15"	5½"	3"	1A:10B:C	24160B
468001K	5 lb ABC w/ Vehicle Bracket	5 lb	8.63 lb	15"	71/4"	41/4"	3A:40B:C	24530B
468002K	10 lb ABC w/ Wall Hook	10 lb	17.44 lb	191/8"	7¾"	51/4"	4A:80B:C	366242B
468003K	20 lb ABC w/ Wall Hook	20 lb	31 lb	21%"	91/4"	71/4"	6A:120B:C	292474K



468003K