#### FIRE EXTINGUISHERS 9

151

2. E. 7

# NON-MAGNETIC WATER MIST FIRE EXTINGUISHERS

These water mist extinguishers contain de-ionized water (sold separately) making them the best extinguishers for protection of hospital environments, valuable books and documents, telecommunication facilities and "clean room" manufacturing facilities. MR conditional-non-magnetic, construction tested by an independent agency for use in MRI facilities to 11.7 Tesla (including wall hanging bracket). AME NOTE: Units ship empty.

Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N
270NMAX	1.75 gal Water Mist w/ Wall Hook	7 lb	24½"	11"	7"	2A:C	-
272NMAX	2.5 gal Water Mist w/ Wall Hook	8 lb	27½"	11"	7"	2A:C	-

### CO<sub>2</sub> FIRE EXTINGUISHERS

The right choice for data processing centers, labs, telecommunication rooms, food storage, processing areas, and other places where contamination and/or clean up is a concern, these CO<sub>2</sub> models use liquefied gas, which effectively fights Class B and C fires.

escription	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket
Jan Farter 5 lb CO and Wall Haals					5	P/N
dger Extra 5 lb CO₂ w/ Wall Hook	15 lb	17"	8½"	51/4"	5B:C	270191K
dger Extra 10 lb CO₂w/ Wall Hook	30 lb	195/16"	1015/16"	615/16"	10B:C	290511K
dger Extra 15 lb CO₂w/ Wall Hook	40 lb	26"	1015/16"	615/16"	10B:C	290511K
dger Extra 20 lb CO₂w/ Wall Hook	51 lb	26"	12"	8"	10B:C	294147K
dde Pro 5 lb CO₂w/ Wall Hook	15 lb	17"	8½"	5¼"	5B:C	270191K
dde Pro 10 lb CO₂w/ Wall Hook	30 lb	19%"	10%"	6%"	10B:C	290511K
dde Pro 15 lb CO <sub>2</sub> w/ Wall Hook	40 lb	26"	10%"	6%"	10B:C	290511K
dde Pro 20 lb CO₂ w/ Wall Hook	51 lb	26"	12"	8"	10B:C	294147K
	lger Extra 10 lb CO <sub>2</sub> w/ Wall Hook lger Extra 15 lb CO <sub>2</sub> w/ Wall Hook lger Extra 20 lb CO <sub>2</sub> w/ Wall Hook lde Pro 5 lb CO <sub>2</sub> w/ Wall Hook lde Pro 10 lb CO <sub>2</sub> w/ Wall Hook lde Pro 15 lb CO <sub>2</sub> w/ Wall Hook	Iger Extra 10 lb CO, w/ Wall Hook 30 lb   Iger Extra 15 lb CO, w/ Wall Hook 40 lb   Iger Extra 20 lb CO, w/ Wall Hook 51 lb   Ide Pro 5 lb CO, w/ Wall Hook 15 lb   Ide Pro 10 lb CO, w/ Wall Hook 30 lb   Ide Pro 15 lb CO, w/ Wall Hook 40 lb	Image: Bit Strain   Image: Bit Strain	Image: Bit Strain   Image: Bit Strain	Idger Extra 10 lb CO, w/ Wall Hook   30 lb   19% "   101% "   61% "     Idger Extra 15 lb CO, w/ Wall Hook   40 lb   26"   101% "   61% "     Idger Extra 20 lb CO, w/ Wall Hook   51 lb   26"   12"   8"     Idger Extra 20 lb CO, w/ Wall Hook   15 lb   17"   8½"   5¼"     Idger Pro 10 lb CO, w/ Wall Hook   30 lb   19% "   10% "   6%"     Idger Pro 15 lb CO, w/ Wall Hook   40 lb   26"   10% "   6%"	Image: Box of the second se

### **DID YOU KNOW?**

Although foam fire extinguishers are rated for use on both Class A and Class B fires, they are normally installed where a spill or pool-type fire could occur. When foam is applied from an extinguisher, it will naturally spread across the burning liquid surface, effectively smothering the fire. If the flammable liquid vapor is prevented from contacting air, the fire is extinguished. Although re-ignition is a possibility with other extinguishing agent applications, it is nearly impossible due to the foam blanket preventing fuel vapors from contacting air.

### FOAM FIRE EXTINGUISHERS

Thanks to their air aspirated nozzles, these units offer an easy and effective defense against Class A and B fires. They're ideal for use in emergency first response vehicles. NOTE: Units ship empty.

Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N
250AX	2.5 gal AFFF Foam w/ Wall Hook	11 lb	24½"	9"	7"	3A:20B	12032AX
254AX	6 L AFFF Foam w/ Wall Hook	7.5 lb	19"	8"	7"	2A:10B	12032AX

# **UNIVERSAL ULTRA FOAM FIRE EXTINGUISHER**

Effective on both Class A and B fires, this extinguisher eliminates the application guesswork associated with other foam units. Its chemical has no offensive odors and is non-toxic, environmentally friendly, and biodegradable. Its also easy to clean up. NOTE: Unit ships empty.

Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N
23697B	2.5 gal AR-AFFF Foam	12 lb	24½"	8¾"	7"	1A:30B	292474K

**Detection Products** Fire Safety &









23697B

250AX

AME