FIRE EXTINGUISHERS

Part No

Description

WET CHEMICAL & WATER FIRE EXTINGUISHERS





Designed to supplement commercial kitchen fire suppression systems, Wet Chemical units are easy to use and very effective in fighting difficult cooking-media fires. The original firefighting tool, these Water units perform better, last longer, and are the number one choice for virtually all hazards where class A-type materials may be present.

Unit

Unit

Shell

Rating

Retention

Ship



		Wt	Ht	Width	Dia		Bracket P/N
25064B	Badger Extra 6 L Wet Chemical w/ Wall Hook	15 lb	19½"	8¾"	7"	K	23131B
23171B	Badger Extra 2.5 gal Wet Chemical w/ Wall Hook	19 lb	24½"	8¾"	7"	K	292474K
Part No	Description	Ship	Unit	Unit	Shell	Rating	Retention Bracket P/N

	Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating	Retention Bracket P/N	
	16888B	Badger Extra 2.5 gal Water w/ Wall Hook (Ships Empty)	8 lb	24¾"	8¾"	7"	2A	292474K	
	466403K	Kidde Pro 2.5 gal Water w/ Wall Hook (Ships Empty)	8 lb	24¾"	8¾"	7"	2A	292474K	
	04795K	Metal Charging Adapter (For Water & Wet Chemical Extinguishers)							





(ITCHEN FIRE EXTINGUISHER RESSP

UL listed to 711A (residential cooking equipment), this special purpose extinguisher meets NFPA 10 and features a proprietary nozzle design for a broad, dispersed discharge of agent. It also delivers it at a high volume, low velocity.


Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	UL Listing	Retention Bracket P/N
21008173K	2.5 lb BC w/ Wall Hook	3.9 lb	13¾"	4½"	31/4"	711A*	420118K

*Residential Cooking Equipment

21008173K

CLASS D DRY POWDER FIRE EXTINGUISHER

Designed for use on combustible metal fires, this dry powder unit is fitted with a "soft-flow" extension applicator. This "tip" keeps the operator away from extreme heat and toxic fumes caused by burning material. Unit comes with a special corrosion-resistant yellow (Class D) color-coded paint finish too. FM approved.





WHEELED STORED PRESSURE PORTABLES

Offering economical protection, these wheeled units are designed for single-person operation and to pass easily through standard doorways. They also contain the highest percentage of essential base ingredients found in the industry, making them ideal for protecting commercial and industrial property from many forms of high-risk fire hazards.

Part No	Description	Ship Wt	Unit Ht	Unit Width	Shell Dia	Rating
20127B	50 lb ABC w/ 25' Hose	140 lb	461/4"	23"	23"	20A:160B:C
20180B	50 lb PK w/ 25' Hose	140 lb	461/4"	23"	23"	160B:C
20653B	125 lb ABC w/ 50' Hose	300 lb	58"	28"	39¼"	40A:240B:C
20684B	125 lb PK w/ 50' Hose	300 lb	58"	28"	39¼"	240B:C

