

## 6 | FIRE EXTINGUISHERS

### AUTOMOTIVE FIRE EXTINGUISHERS

For an extra measure of safety for cross-country or cross-town trips, these automotive models can extinguish fires in seconds.



440162K

| Part No   | Description   | Net Agent Wt (Avg) | Ship Wt | Unit Ht             | Unit Width        | Shell Dia         | Rating   | Retention Bracket P/N |
|-----------|---|--------------------|---------|---------------------|-------------------|-------------------|----------|-----------------------|
| 440162K   | Fire Control FC110 2.5 lb ABC w/ Plastic Strap Bracket  | 2.4 lb             | 3.9 lb  | 14 $\frac{1}{16}$ " | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 1A:10B:C | 420118K               |
| 466423K   | Fire Control FC110M 2.5 lb ABC w/ Metal Valve, Plastic Bracket and Metal Strap (Rechargeable) | 2.4 lb             | 3.9 lb  | 14 $\frac{1}{4}$ "  | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 1A:10B:C | 466401K               |
| 466425K   | Fire Control FC340M-VB 5 lb ABC w/ Metal Valve, Metal Bracket and Metal Strap (Rechargeable)  | 5.5 lb             | 8.4 lb  | 16 $\frac{7}{8}$ "  | 5 $\frac{3}{4}$ " | 4 $\frac{1}{2}$ " | 3A:40B:C | 466400K               |
| 440160K   | Fire Control FC5 2 lb BC w/ Plastic Strap Bracket   | 2 lb               | 2.6 lb  | 11 $\frac{1}{16}$ " | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 5B:C     | 420118K               |
| 440161K   | Fire Control FC10 2.5 lb BC w/ Plastic Bracket and Metal Strap                                | 2.5 lb             | 3.9 lb  | 14 $\frac{1}{16}$ " | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 10B:C    | 420118K               |
| 466422K   | Fire Control FC10M 2.5 lb BC w/ Metal Valve, Plastic Bracket and Metal Strap (Rechargeable)   | 2.5 lb             | 4.4 lb  | 14 $\frac{1}{4}$ "  | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 10B:C    | 466401K               |
| 21006287K | Auto FX II 2 lb BC w/ Plastic Strap Bracket (Gray Color Cylinder)                             | 2 lb               | 2.6 lb  | 11 $\frac{1}{16}$ " | 4 $\frac{1}{2}$ " | 3 $\frac{1}{4}$ " | 5B:C     | 420118K               |



### AUTOMOTIVE EXTINGUISHERS



In 2013, there were 164,000 highway vehicle fires resulting in over \$1.1 billion in direct damages. The DOT requires vehicles used to transport hazardous materials in a quantity that requires placarding must be equipped with a fire extinguisher having an UL rating of 10B:C or more. A vehicle that is not used to transport hazardous materials must be equipped with either a fire extinguisher having UL ratings of 5B:C or more; or two fire extinguishers, each of which has a UL rating of 4B:C or more.

FMCSA. *Parts & Accessories Necessary for Safe Operation.* [fmcsa.dot.gov/regulations/title49/section/393.95](http://fmcsa.dot.gov/regulations/title49/section/393.95). 2017.



417TCAX

### MULTI-PURPOSE CHROME FIRE EXTINGUISHERS

Multi-purpose units effectively fight Class A, B, and C fires and are a popular choice for vehicles and watercraft. They have the highest UL rating per size and are attractive and easy to maintain.

| Part No | Description                          | Net Agent Wt (Avg) | Ship Wt | Unit Ht            | Unit Width        | Shell Dia         | Rating   | Retention Bracket P/N |
|---------|--------------------------------------|--------------------|---------|--------------------|-------------------|-------------------|----------|-----------------------|
| 417TCAX | 2.5 lb ABC w/ Vehicle/Marine Bracket | 2.5 lb             | 5.5 lb  | 15 $\frac{1}{2}$ " | 5 $\frac{3}{4}$ " | 3"                | 1A:10B:C | 817AX                 |
| 500TCAX | 5 lb ABC w/ Vehicle/Marine Bracket   | 5 lb               | 9.5 lb  | 15 $\frac{1}{4}$ " | 7 $\frac{1}{4}$ " | 4 $\frac{1}{4}$ " | 2A:10B:C | 12313AX               |



### CHROME DRY CHEMICAL FIRE EXTINGUISHER

Perfect for kitchens, garages, boats, and vehicles, it is designed for combating flammable liquid and pressurized gas fires. Plus it is electrically non-conductive and will not bake to hot surfaces, allowing for easy clean up.



620TCAX

| Part No | Description                | Net Agent Wt (Avg) | Ship Wt | Unit Ht | Unit Width        | Shell Dia         | Rating | Retention Bracket P/N |
|---------|----------------------------|--------------------|---------|---------|-------------------|-------------------|--------|-----------------------|
| 620TCAX | 1 lb BC w/ Vehicle Bracket | 1 lb               | 2.5 lb  | 10"     | 3 $\frac{1}{2}$ " | 2 $\frac{1}{2}$ " | 2B:C   | -                     |