

ΔRH

PAR36 Aluminum Remote Head

DATE:	COMMENTS:
PROJECT	

FEATURES

- The ARH is ideal for industrial environments and installations where the fixture will be exposed to constant excessive temperatures or UV exposure
- Rotary locking collar securely locks the lens and reflector assembly into place
- Innovative design allows for quick and easy re-lamping
- Designed to fit standard junction boxes
- Adjustable swivel lock secures the head in place once adjusted





ORDERING INFORMATION ARH-BA-1-L126

1. SERIES	2. HOUSING COLOR	2. HEAD COUNT	3. LAMP SOURCE	4. OPTIONS

- BA
BA Brushed Aluminum

One Head
 Two Heads
 Three Heads

See Lamp Chart for Part # Example: LED 12V 6W = "L126"

BLANK = NO OPTION

LF Food-Prep Lens (Shatter-Resistant Coating)

ACCESSORIES; ORDER SEPARATELY

ARH

- WG 8 = Wire guard 8.0" X 6.0" X 8.0"
- WG 9 = Wire guard 12.0" X 9.0" X 9.0"

SPECIFICATIONS

CONSTRUCTION

- Lamp Head constructed of durable spun aluminum
- Thermoplastic canopy
- Glass lens will not yellow over time

APPROVALS

- UL924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty.
 For further details, refer to General
 Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

LAMP CHARTS

B - BI-PIN HALOGEN					
	6V	12V	24V		
6W		B126			
8W	B68	B128			
10W	B610				
12W	B612	B1212			
20W	B620	B1220	B2420		
35W		B1235			
55W		B1255			
70W			B2470		

L - LED			
	12V	24V	
6W	L126	L246	