

FEATURES

- Dual voltage input 120/277 VAC, 60Hz
- Black powder-coat painted, die-cast canopy provided
- All components, including battery and electronics, located internally
- REUS Series Exit can be universally surface mounted
- Universal J-box mounting pattern
- High-impact, clear acrylic panel
- Clear single face or mirrored double face panels are standard
- Bright red letters


• Universal field-installable chevrons in bright red and green

ENERGY DATA

See Specification Sheet for Energy Data

Compliances may not apply to all product configurations. Please consult the product spec sheet for compliance details.

COMPLIANCES: UL924 Listed; NFPA 101 Compliant, NYC Code Compliant



ORDERING INFORMATION

SIGN

SAMPLE NUMBER: REUSA18R

Family	Mounting	Battery	Face Options	Letter Color
REU=Rival Edge-Lit	S =Surface	A=AC-Only N=Self-Powered	18=Single Face, 8" Letters 28=Double Face, 8" Letters	R =Red



REUR - RECESSED

EDGE-LIT EXIT

SIGN

FEATURES


- Dual voltage input 120/277 VAC, 60Hz
- Black powder-coat painted, die-cast canopy provided
- All components, including battery and electronics, located internally
- Universal J-box mounting pattern
- High-impact, clear acrylic panel
- Clear single face or mirrored double face panels are standard
- Bright red letters
- Universal field-installable chevrons in bright red and green
- Solid-state Voltage Limited Charger, Brownout Circuit Protection

ENERGY DATA

See Specification Sheet for Energy Data

Compliances may not apply to all product configurations. Please consult the product spec sheet for compliance details.

COMPLIANCES: UL924 Listed; NFPA 101 Compliant, NYC Code Compliant



ORDERING INFORMATION

SAMPLE NUMBER: REURA18R

Family	Mounting	Battery	Face Options	Letter Color
REU=Rival Edge-Lit	R=Recessed (Accessible Ceiling Only)	A=AC-Only N=Self-Powered	18=Single Face, 8" Letters 28=Double Face, 8" Letters	R=Red