


FEATURES

- Dual 120/277 VAC 60Hz input
- Two-step charger
- Line-latched transfer circuit, brownout protection
- "Self-Check" diagnostics
- Sealed, maintenance-free, long-life lead calcium battery
- White powder-coat on 20-gauge cold-rolled steel
- Universal mounting knockouts provided

Compliances may not apply to all product configurations. Please consult the product spec sheet for compliance details.

COMPLIANCES: UL924 Listed; NFPA 101 Compliant, NYC Code Compliant



A COMMERCIAL EMERGENCY LIGHT

ORDERING INFORMATION - NEW YORK CITY

Family	Capacity in Watts (Hours)				Number of Heads	Watts per Head	Max Remote Heads	Replacement Lamp	Dimensions (mm)				Shipping Weight
	1.5	2	3	4					A	B	C	D	
6 VOLT													
6ACNY1	27	-	-	-	2	12	-	6RW12	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	13
6ACNY4	54	44	-	-	2	12	2	6RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
6ACNY5	100	75	50	-	2	12	6	6RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
6ACNY5-3	100	75	50	-	3	12	5	6RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	23
12 VOLT													
12ACNY2	27	-	-	-	2	12	-	12RW12	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	14
12ACNY3-3	36	-	-	-	3	12	-	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	17
12ACNY4	54	44	-	-	2	12	2	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
12ACNY4-3	54	-	-	-	3	12	1	12RW12	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	20
12ACNY5	100	75	50	45	2	12	6	12RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
12ACNY5-3	100	-	-	-	3	12	5	12RW12	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	23

ORDERING INFORMATION - NATIONAL

Family	Capacity in Watts (Hours)				Number of Heads	Watts per Head	Max Remote Heads	Replacement Lamp	Dimensions (mm)				Shipping Weight
	1.5	2	3	4					A	B	C	D	
6 VOLT													
6AC27	27	22	18	-	2	9	-	6RW9	14" (355mm)	10" (254mm)	2-5/8" (67mm)	9" (229mm)	13
6AC54	54	44	36	-	2	9	4	6RW9	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
6AC100	100	75	50	45	2	9	9	6RW9	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22
12 VOLT													
12AC54	54	44	36	-	2	9	4	12RW9	14" (355mm)	13" (330mm)	2-5/8" (67mm)	9" (229mm)	19
12AC100	100	75	50	45	2	9	4	12RW9	14" (355mm)	13" (330mm)	4-1/8" (165mm)	9" (229mm)	22

OPTIONS AND ACCESSORIES

Options: Add to catalog number Description	Code	Accessories: Add to catalog number Description	Code
No Heads	0	Cord Sets	
One Head	1	120 Volt	3 CP
Three Heads	3	277 Volt (specify male plug type)	3 OP
Voltmeter (1)	V	Mounting Bracket (specify model to be used with)	MBI
Ammeter (1)	A		
Time Delay	TD	Mounting Shelf (specify model to be used with)	MS
Non Standard Voltages (consult factory)			
New York City Approved	NY	Wire Guards (consult factory)	

Remote Fixtures (to order see remote fixtures section)

Notes: N.Y.B.S.A. Calendar (approval) #34013.

(1) Units may NOT be equipped with a voltmeter and ammeter at the same time.

(2) When using halogen lamps, total connected lamp load must be at least 80% of 90 min. rating, or premature lamp failure may occur.