

BBDL Series

RAISED BACKSIDE

BROWN YELLOW

RED

H - 1/2" W - 6 1/8"

Backup

LED INDICATOR

& TEST SWITCH

Ultra Thin LED Downlight with Emergency Battery The BBDL is a popular Ultra Thin Profile LED Downlight for versatile installation. Big Beam's unique BBDL comes standard with battery DRIVER H - 1 3/8" L - 4" W - 2 5/8" backup, versions without battery backup are DOWNLIGHT EBBU DRIVER available. Battery Backup minimum runtime of W - 7 7/16" 90 minutes. FIELD SELECTABLE COLOR

3000K-4000K-5000K

FEATURES

4", 6", & 8"

- 120-277V
- 4W or 10W Emergency Battery Backup & Test Switch

TEMPS OF 3000K- 4000K-5000K. Available in

- Field Selectable Color Temps of 3000K, 4000K and 5000K. Dip Switch on the Battery Backup box Field Selectable Color Temps
- SMD 2835, CRI 80

Standard with White Trim

Junction box included

Damp rated; suitable for bathroom installations.

- LED fixture, junction box and Battery Backup are detachable.
- Edge lit technology eliminates hot spots, smooth 3" wide spread,
- Dimmable with most wall/box dimmers.
- Approved by ETL Standards for Canada and USA.
- Extruded Aluminum Housing with Polycarbonate lens.
- Stainless steel locking mechanisms.

NEUTRAL WHITE LINE YELLOW/BLACI **Emergency Driver** Battery BLACK **Emergency Pack** DRIVER MUST BE GROUNDED WALL SWITCH

Test


Switch


WARRANTY

5 Year Warranty

IC RATED







Hole-Cut Size:

LED Driver

6 1/2" ± 1/8" 4 3/4" ± 1/8"

 $165 \pm 3 \, \text{mm}$

205 ±3 mm

8" ±1/8"

PURPLE V+ 0~10V V- DIMMER

10V

 $95 \pm 3 \, \text{mm}$

4"

WHITE

BLACK

6"

8"

Series	Size	Battery Backup	Options
BBDL	4 = 4" (9W, 630lms)	4 = 4W	-NBBU = No Battery Backup
	6 = 6" (16W, 1120lms)	10 = 10W	
	8 = 8" (18W, 1260lms)		

