

Commercial Emergency Lights

Series Features




- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
120VAC 60 Hz 1.5W/277VAC 60 Hz 1.5W



- High-Intensity Tungsten Lamps, 6-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Meets ADA: American Disabilities Act
- Compact Design
- Flame-Retardant Housing
- Universal Mount, Polycarbonate Backplate
- High-Impact, Mist White Finish
- Red (Power On) LED Indicator
- Test Switch
- Damp Location
- UL Listed

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
BBEM-6	6	12	9	6	-	-	-	-	-	(1) S65
BBEM-L	1.25	12	9	9	-	-	-	-	-	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours.
NEC requires 1.5 hours of emergency illumination.

BBEM



Ordering Information

BBEM-6
Series



Dimensions BBEM-6

Height: 4.25"
Width: 14.0"
Depth: 3.5"

Options

Add Suffix to Catalog Number

- BLK Black Finish
- P2 Cord & Plug for 120VAC Input
- LED White LED Lamps
- SD Self Diagnostic