



X40 Recessed Ceiling Only **Prestige Series**

Premium Die Cast Flat Trim Plate Edge-Lit Exit Sign

X40 Prestige Series is designed for recessed ceiling mounting applications requiring a flat trim plate. Available in AC-Only and Self-Powered models. For recessed wall mounted signs see page 44-45.

UL Listed

UL listed to standard 924

Light Sources

- LED, Light Emitting Diodes

Sealed Maintenance-Free Batteries

- Nickel Cadmium

Standard Features

Reliability

The X40 Prestige Series has a 5-year full warranty.

Unit Data

The clear acrylic panel is silk screened and computer engraved. The rugged cast brushed aluminum trim plate (optional colors available) is designed to fit integrally with a 20 gauge steel back box. Each unit includes a bar hanger kit.

Charger

Circuitry offers 120/277 volt input, fully automatic charger, temperature compensated charger, sealed relay, low voltage battery disconnect, and brownout protection.

Advanced Optical Technique

The Prestige Series is designed to achieve superior visual clarity and performance with an LED light Source.

- Two rows of high brightness LEDs transmit light directly into both ends of a unique U-shaped panel.
- Virgin acrylic panel provides optimum light transmission.
- LED sensitive inks are formulated to provide a rich color in red or green.
- Computer engraving is used to crisply define each letter and chevron.
- Choice of legend background includes: Clear (for single face), White or Mirror (for single or double face signs).
- Illumination is 100% in both AC and the emergency mode.

How To Order (example)

W	LSNX	42	RC	AR	D
Trim Plate Color	Model	Number of faces	Letter/background colors	Arrow designation	Options
Blank = Brushed aluminum other colors available see optional features	LX = AC-only LSNX = Self-powered	42 = Single face 43 = Double face	RC* = Red on clear RW = Red on white RM = Red on mirror GC* = Green on clear GW = Green on white GM = Green on mirror *Available single face only	Blank = No arrow AR = Arrow right AL = Arrow left DA = Double arrow ARL = Arrow right and left, used on double face signs with one arrow on each side	See optional features
B = Black W = White BR = Dark bronze PB = Polished brass CH = Chrome					



LED Light Source Benefits

Low Energy Consumption: LED lamps consume only 3 watts, per sign, single or double face.

No Maintenance Cost: Long life LED's eliminate twice-a-year relamping typical of incandescent lamps.

Reliability: Prestige LED Series signs are unaffected by the vibrations, ambient temperature swings and typical power surges detrimental to standard exit light sources.

Optional Features

Description	Add Suffix
8" lettering for NYC code	8
Special phrase engraved on panel.....	Contact Factory
Dual circuit operation (AC-only)2CKT
Self testing/self diagnostic (self-powered only).....	D

Accessories (order as a separate item)

Two 27" adjustable bar hangers*TBH

*Bar hangers supplied with unit, sold as replacement only.

Outline and Dimensions

Dimensions are approximate and subject to change.

Trim plate: 16"L X 4"W
Faceplate: 13"L X 7 5/8"H
 (faceplate height is measured from the bottom of the plate to the ceiling, including trim plate depth.)
Recessed Back Box: 15"L X 3 3/8"W X 3 3/4"D

