

# Chicago Approved LED Exits

CHL



CHL / ECHL

## Dimensions

### CHL / ECHL

Height: 9.5"  
Width: 12.3"  
Depth: 2.0"

## Options

Add Suffix to Catalog Number

-TP Tamper-Proof Screws  
-STAIR "STAIR" Legend in Lieu of "EXIT"  
-STAIRS "STAIRS" Legend in Lieu of "EXIT"

## Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)  
P12W 12" Pendant Kit, White\*



Made in USA

## Series Features

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) Standard 1.7 Watts
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Open-Face Glass Panel
- Silk Screen Letters
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Chicago Code Approved
- UL Listed

## Additional Emergency Unit Features

- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free
- 3+ Hours Illumination in Emergency Mode\*
- Test Switch
- LED (Power On) Indicator


\*Longer Illumination Times Available. Consult Factory.

## Specify Arrow Configuration on all Open-Face Signs

Blank = No Arrow

AR = Arrow Right


AL = Arrow Left



DA = Dual Arrow

ARAL = Arrow Right/  
Arrow Left

(Double-Face Only – 1 Arrow per Face)



## Ordering Information

CHL	1	R	W	W	-TP
CHL-AC Only ECHL – Emer.	# Faces 1 2	Letter Color Red	Panel Color White	Housing Color White* Black PM Painted Matte Chrome	Option Factory Options