



DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

tradeSELECT^{*}



RELATED PRODUCTS

8 CU2W - Wet Location LED Emergency Unit

FEATURES

- The CWR remote lamps are driven exclusively by the Compass CU2W with remote capacity
- Quick installation
- UL924 listed for 10°C to 40°C (50°F to 104°F)

SPECIFICATIONS

DESCRIPTION

- The CWR single and double remote heads offer quality and value with a compact and attractive LED based outdoor remote emergency light
- Includes mounting base and lampheads in durable die-cast construction. Lampheads are fully gasketed, fully adjustable and glare-free for operation in outdoor and wet environments
- The CWR remote lamps are driven exclusively by the Compass CU2W with remote capacity.

APPLICATION

• The CWR remote heads can be applied over path of egress doors in areas affected by rain, moisture and condensation

APPLICATION

UL924

WARRANTY

- · 2 year full unit warranty
- See <u>HLI Standard Warranty</u> for additional information


ORDERING GUIDE

Catalog Number	Description	Voltage	Lamp Watts (Each)
CWRS	Single-head LED Remote CU2W Only, Grey Finish	9.6Vdc	1.OW
CWRD	Double-head LED Remote for CU2W Only, Grey Finish	9.6Vdc	1.0W




CU2W Emergency Light

DIMENSIONS



Single Carton Weight (single)	2 lbs.
Single Carton Weight (double)	2 lbs.
Master Carton Quantity	12 each

CWRS 4.5" 2.6' 10"



Photometric files available for download at www.compasslightingproducts.com Outlet box must have a minimum depth of 3" (Not Included)