

DATE:

COMMENTS:

PROJECT




## FEATURES

- Combines two Eco-friendly technologies: LED and Photoluminescence
- Maintenance-free LED light source illuminates the letters in normal AC power
- Non-electrical Photoluminescence illuminates the letters when AC power fails
- Requires only 2 Watts of electrical power
- Eliminates the need for any auxiliary power or external charging light sources
- No batteries required
- Polycarbonate security cover and wire guards available
- Vandal resistant and tamper proof polycarbonate shield available
- Recessed power supply for all units
- Zero current, low-voltage disconnect
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- 120/277 VAC field-selectable inputs



## ORDERING INFORMATION *DTH-G-1-BA-BA-MB*

### 1. SERIES

**DTH**

### 2. ILLUMINATION

**G**

**G** Green

### 3. FACE COUNT

- 1 Single
- 2 Double

### 4. FACE COLOR

- BA** Brushed Aluminum
- BK** Black
- WH** White

### 5. FRAME COLOR

- BA** Brushed Aluminum
- BK** Black
- WH** White

### 6. MOUNTING

- MB** Back Mount
- MRW** Recessed Wall Mount
- MPA** 12" Swivel Pendant Kit
- MPB** 24" Swivel Pendant Kit
- MPC** 36" Swivel Pendant Kit
- MPD** 48" Swivel Pendant Kit
- MTEB** Top/End/Back Mount

### 7. OPTIONS

- BLANK = NO OPTION**
- LD** Damp Location
- TP** Tamper proof Screws
- VRA** Vandal Resistant Lens (1/8 in) (Incl. TP)
- VRB** Vandal Resistant Lens (1/4 in) (Incl. TP)

## ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard 14" X 10" X 4.5"
- WG 3 = Wireguard 14.5" X 6" X 10.5"
- WG 10 = Wireguard 13.5" X 12" X 16.5"

## CONSTRUCTION

- Injection molded internal cavity reflector provides ease of installation and maintenance together with perfectly even legend illumination
- Two piece, heavy-duty walls constructed from die cast aluminum alloy
- Removable front stencil face with overlapping light seal
- Hidden knock out access points and universal pattern
- Optional recess frame, polycarbonate face shield with tamper proof access screws, and pendant & specialty mounts

## LETTERS

- 6" high; 0.75" stroke

## ARROWS

- NFPA type, universal field-selectable chevrons

## WEIGHT

- 4.5 lbs

## CANOPY SIZE

- 4.75" x 4.75" x 0.75"

## APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70- NEC
- OSHA

## WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

## DIMENSIONS

