

DATE:	COMMENTS:
PROJECT:	

## FEATURES

- Ultra-bright, energy efficient, long-life Red or Green LEDs
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- 4.8V long-life, maintenance-free, rechargeable Ni-Cad battery
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 120/277 VAC field-selectable inputs (with the exception of the CX (dual circuit) option)



## ORDERING INFORMATION *EDC-EM-G-U-BA-BA-MTEBP*

1. SERIES	2. OPERATION	3. COLOR	4. FACES	5. FACE COLOR	6. FRAME COLOR	7. MOUNTING
EDC	-	-	-	-	-	MTEBP
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black WH White	BA Brushed Aluminum BK Black WH White	MTEBP Universal Mount

## 8. OPTIONS

**BLANK = NO OPTION**

SD Self-Diagnostics<sup>1</sup>

CX Dual Circuit - 120/277 VAC<sup>2</sup>

TP Tamperproof Screws

## ORDERING NOTES

1. EM Operation only

2. AC Operation only. This dual circuit option should only be used for exits which are intended to be connected simultaneously to normal and emergency power circuits, but cannot support two hot inputs. Only one of the normal or emergency circuits can be powered at any given time. Energizing both normal and emergency circuits simultaneously will result in damage to the exit sign.

## ACCESSORIES; ORDER SEPERATELY

- WG 2 = Wireguard Wall Mount 14" X 10" X 4.5"
- WG 3 = Wireguard Ceiling Mount 14.5" X 6" X 10.5"
- WG 10 = Wireguard End Mount 13.5" X 12" X 16.5"

## SPECIFICATIONS

### CONSTRUCTION

- Premium-grade, aluminum housing. Also available in black or white powder-coat finishes

### ELECTRICAL

- Input Power: 4.4W Max

### ARROWS

- Field selectable knockout chevron directional indicators

### DIMENSIONS

### WEIGHT

- 5 lb

### APPROVALS

- UL 924
- UL Listed for Damp Location
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

### TEMPERATURE RATING

- From 32°F to 122°F

### WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

