EZXTEU-RC Remote Capable LED Exit Sign



Project:	
Type:	
Catalog #:	

STANDARD











ILLUMINATION

Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

- Dual 120/277 voltage.
- Offers 11W of remote capacity standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and remote lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.




OPTIONS

HTR: Optional internal heater for cold temperature $(-9^{\circ}C - 50^{\circ}C)$ applications.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets CSA C22.2 No. 141-02 requirements for unit equipment.
- UL Listed for damp locations (20°C 50°C).
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



Sample Part Number: EZXTEU2RWEMRC

ORDERING INFORMATION

MODEL	No. of FACES LETTER COLOR		HOUSING COLOR		BATTERY				OPTIONS			
EZXTEU	2	Universal Single/Double Face	R G	Red Green	W B	White Black	EM	Battery Backup	RC	Remote Capable Standard	HTR	internal Heater

Special voltage & SALIDA face plate options available. Check with your Best Lighting Representative.

EZXTEU-RC Remote Capable LED Exit Sign



Project:	
Type:	
Catalog #:	

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT V	VATTS (W)	INPUT AMPS (A)			
	120V	277V	120V	277V		
EZXTEU-RC/RC	10	10	0.10	0.05		

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE	COMPATIBLE REMOTE HEAD FAMILY											
		CAPACITY	MRHLED	RHLED	RH16LED	RH16		RH		RHR		SRH		SRHLED
				MV		6V	12V	6V	12V	6V	12V	6V	12V	
EZXTEU-RC/RC	6V	11W		Х	Х	Χ		Χ		Х		Χ		Х