







LED Full Cutoff Emergency Wall Pack

Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC)
120/277 VAC 18 Watts / 60Hz
- (8) LG SMD 4000K LED's
- 1600 Lumens in AC Mode / 600 Lumens in Emergency Mode
- Integral photocell - Operates as a dusk to dawn luminaire in AC Mode
- Full Cut-Off optics for Dark Sky Compliance
-  • Back Wall Mount on Junction Box or surface conduit
- Die Cast Aluminum Housing with premium heat sink
- Polyester Powder Coat Paint Finish
- Bronze color standard (contact factory for other color options)
- UV resistant polycarbonate lens
- Suitable for Indoor or Outdoor Applications
- Self Diagnostic Standard

Additional Emergency Unit Features

-  • Maximum Input Rating (120 or 277VAC)
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Voltage Surge Protection
-  • 7.2V Nickel Cadmium Maintenance-Free Battery,
- 5-Year Pro-Rated Battery Warranty
- Battery Heater Standard for Cold Locations (-40°F)
- 24 hour recharge after full discharge
-  • 1.5+ Hours Illumination on Battery Power
- Test Switch / AC on Power Indicator Light
- UL924 Listed for Wet Locations
- IP65 Rated
- DLC Listed

FCL



Shown in Standard Dark Bronze Finish

Dimensions

FCL
Height: 6.25"
Width: 9.00"
Depth: 2.50"

Unit operates as a dusk to dawn luminaire with integral photocell as well as an emergency light in the event of power failure

Options

Add Suffix to Catalog Number

-PIR Passivive Infrared Motion Sensor
(non stock special order)



Ordering Information

FCL	DB	-PIR
Model	Housing Color	Options
FCL-EM – General & Emergency Lighting	DB Dark Bronze WH White (non standard special order) BK Black (non standard special order) NK Nickel (non standard special order)	-PIR