



FHEX23




Recessed Aluminum LED Edgelit Exit

- Push-to-test switch
- LED charge indicator
- AC and EM models
- Field applied chevron directional indicators
- Maintenance free, 3.6V, 500mAh NiCd battery
- Compatible with drop ceiling mount installations. Bar hangers included
- Energy saving LED lamp source
- Dual voltage 120V/277V
- UL Listed in accordance with UL924
- Ideal for stores, offices, hospitals and school corridors.


General Specifications

	FHEX23 (Red)	FHEX23 (Green)
Input Voltage	120/277VAC	120/277VAC
Input Current (120V)	27mA	27mA
Input Current (277V)	12mA	12mA
Input Power (120V)	3.0W	3.0W
Input Power (277V)	3.0W	3.0W
Operating Frequency	60Hz	
Battery Type	3.6V, 500mAh NiCd Battery	
Operating Ambient Temperature Range (Ta)	0°C to 50°C / 32°F to 122°F	
Overall Size	12.6" L x 8" H	
Emergency Operation	90 minutes	
Compliance	UL 924 Listed	
	Damp Location	
Warranty	5 years from the date of manufacture	

Mechanical Data



FRONT VIEW



SIDE VIEW

NOTE:

- 1) In order to maintain proper operation and warranty coverage, the battery must be recharged once per year prior to installation.

Part Number Matrix

FHEX23

A

S

R

EM

Case Color
A = Aluminum
W = White

Number of Faces
S = Single
D = Double

Letter Color
R = Red
G = Green

Operation
EM = Battery Backup