

## GLO BRITE® FRAMED EXIT/SORTIE SIGNS

### *The Next Generation in Exit Sign Technology*

#### **A component of the Glo Brite® Safety Guidance System of photoluminescent products**

Unparalleled in reliability, Glo Brite® Exit Signs utilize the latest photoluminescent technology to absorb and store ambient fluorescent light. In the event of an emergency with blackout or smoky conditions this stored energy is immediately visible, creating a clearly recognizable, photoluminescent egress indicator. Glo Brite® Exit Signs reduce the risk of panic or injury during an evacuation, offering greater peace of mind while saving on energy costs.

#### **Features**

- Requires no additional electricity to operate
- Reliability
- Non-toxic, non-radioactive
- Low-cost, easy installation
- Designed for surface, flag or ceiling mounting
- Can be used for both high-level and low-level applications
- Requires virtually no maintenance, periodic inspections, for 25+ years
- Thin, low profile construction
- Consistent, uniform illumination
- Visible at 50 feet in total blackout
- Saves on energy costs
- Listed to UL 924 through UL, ICC ES #6040 meeting all current building codes, meets NFPA Life Safety Code 101 and OSHA requirements
- CCMC Evaluation Report CCMC 13211R

#### **Technical Information**

- Sizes: 8" x 15" x 1/4" (Sortie 8" x 22.1875" x 1/4")
- Letter Size: 7/8" stroke with 7" height
- Background: Black, Red, Green or White
- Illumination: High Visibility Green
- Visibility: 50 feet
- Directional: Pop-out chevron arrows for easy direction selection
- Construction: .035 steel and a plastic photoluminescent panel
- Durability: Explosion-proof for areas requiring explosion-proof exit signage
- Tests Passed: UL 924 Emergency Lighting and Power Equipment Listed through UL; ICC ES # 6040; California State Fire Marshall listing #6200-1617; 100; City of Los Angeles Research Report: RR 25531 (CSI #16530); Ontario Building Material Evaluation Commission Authorization Report BMEC #03-12-291; CCMC 13211-R

- Life Expectancy: 25+ years
- Power Requirements: NO additional electrical or mechanical source required
- Installation: Surface, flag or ceiling mounted (hardware included). Before installation it must be determined that there is a minimum of 54 lux of fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.
- Applications: Both high-level and low-level

#### **Models Available:**

| Exit Black | Exit Red                                     | Exit Green | Exit White | Sortie Red |  |
|------------|--|------------|------------|------------|--|
| 7001       | 7011   | 7021       | 7031       | 7013       | Single face sign (wall mount)          |
| 7001 - B   | 7011 - B                                     | 7021 - B   | 7031-B     | 7013-B     | Single face sign with mounting bracket |
| 7002 - B   | 7012 - B                                     | 7022 - B   | 7032-B     | 7014-B     | Double face sign with mounting bracket |
| 7000 - B   | 7010 - B                                     | 7020 - B   | 7030-B     | 7010-B     | Mounting bracket                       |
| 7000 - B2  | Clear mounting clip (4 pc/bag & 10 bag/case) |            |            |            |  |

Other photoluminescent components of the Glo Brite® Safety Guidance System include Glo Brite® Egress Pathway Strips, Glo Brite® Tape, Glo Brite® Dots and Arrows, Glo Brite® Stripe Tape, Glo Brite® Safety Track, and Glo Brite® Safety Signage.





7210



7220



7310



7320



7211

## GLO BRITE® UNFRAMED EXIT/SORTIE SIGNS

*The Next Generation in Exit Sign Technology*

**A component of the Glo Brite® Safety Guidance System of photoluminescent products**

Unparalleled in reliability, Glo Brite® Exit Signs utilize the latest photoluminescent technology to absorb and store ambient fluorescent light. In the event of an emergency with blackout or smoky conditions this stored energy is immediately visible, creating a clearly recognizable, photoluminescent egress indicator. Glo Brite® Exit Signs reduce the risk of panic or injury during an evacuation, offering greater peace of mind while saving on energy costs.

### Features

Requires no additional electricity to operate

Reliability

Non-toxic, non-radioactive

Low-cost, easy installation

Can be used for both high-level and low-level applications

Requires virtually no maintenance, periodic inspections, for 25+ years

Thin, low profile construction

Consistent, uniform illumination

Visible at 50 feet in total blackout

Saves on energy costs

Listed to UL 924 through UL, ICC ES #6040 meeting all current building codes, meets NFPA Life Safety Code 101 and OSHA requirements

CCMC Evaluation Report CCMC 1324-R

### Technical Information

Sizes: 7.5" x 13" x .075" (7280 = 10" x 17" x .075")  
(Sortie 7.5" x 18.125" x .075")

Letter size: .8125" stroke with 6" height (7280 = 1" stroke with 8" height)

Background: Photoluminescent

Illumination: High Visibility Green

Visibility: 50 feet

Directional: 2 included

Construction: Plastic photoluminescent panel/red or green lettering

Durability: Explosion-proof for areas requiring explosion-proof exit signage

Tests Passed: UL 924 Emergency Lighting and Power Equipment

Listed through UL; ICC ES # 6040, California State Fire Marshall

listing #6200-1617; 100; City of Los Angeles Research Report:

RR 25531 (CSI #16530); Ontario Building Material Evaluation

Commission Authorization Report BMEC #03-12-291; CCMC 13211-R

Life Expectancy: 25+ years

Power Requirements: NO additional electrical or mechanical source required


Installation: Surface mounted. Before installation it must be determined that there is a minimum of 54 lux of fluorescent, metal halide or mercury vapor light on the face(s) of the sign at all times during building occupancy.

Applications: Both high-level and low-level

### Models Available:

| Exit Red | Exit Green | Sortie Red |  |
|----------|------------|------------|--|
| 7210     | 7310       | 7211       | Single face sign (wall mount) printed letters    |
| 7220     | 7320       |            | Single face sign (wall mount) reflective letters |
| 7280     |            |            | Single face sign (wall mount) 8" printed letters |

Other photoluminescent components of the Glo Brite® Safety Guidance System include Glo Brite® Egress Pathway Strips, Glo Brite® Tape, Glo Brite® Dots and Arrows, Glo Brite® Stripe Tape, Glo Brite® Safety Track, and Glo Brite® Safety Signage.



© Jessup 2006



© Jessup 2006



CCMC  
13211-R