

Series Features

	<ul style="list-style-type: none"> <li>• Integrated Solid State System</li> <li>• Internal Battery Charger</li> <li>• 12 Hour Recharge Time</li> <li>• Maximum Input Rating 120 VAC 60 Hz 0.35 Amps</li> </ul>
	<ul style="list-style-type: none"> <li>• PAR-36 LED Sealed Beam</li> </ul>
	<ul style="list-style-type: none"> <li>• Sealed Lead Calcium Battery</li> <li>• 6 Volt Operation</li> <li>• Maintenance-Free</li> </ul>
	<ul style="list-style-type: none"> <li>• Rugged 20-Gauge Steel Housing</li> <li>• Safety Yellow Powder Coat Finish</li> <li>• Fully Secured Battery</li> <li>• Full-Length Piano Hinge</li> <li>• Ammeter</li> <li>• External On/Off Switch, One For Each Lamp</li> <li>• Top Mounted Carrying Handle</li> <li>• Detachable 6ft 120V Cord</li> </ul>

Unit Information

Model Number	Std. Lamp Watt	Run Time	Weight	Replacement Battery
HBL6S5	6	1.5 hrs	10 lbs	(1) S65
HBL6S8	6	2.5 hrs	11 lbs	(1) S68
HBL6S10	6	4 hrs	14 lbs	(1) S610SL
HBL6S20	6	8 hrs	20 lbs	(2) S610SL
HBL6S36	6	12 hrs	22 lbs	(1) S636
HBL6S20-20	20	2 hrs	17 lbs	(2) S610SL
HBL6S36-20	20	3.75 hrs	22 lbs	(1) S636
BL12S15-100	100	.75 hrs	22 lbs	(1) S1215

Ordering Information

LS	BL	655	-W
LS-LED H-Halogen*	Series	Battery Voltage	Options

HBL



Portable Industrial Work Light comes in handy in situations where a back-up generator fails to start. Can be positioned anywhere in a facility that requires lighting during an outage – especially in critical areas.

Dimensions

HBL  
Height: 13.5"  
Width: 13.5"  
Depth: 4.75"

Options

Add Suffix to Catalog Number

- W White
- R Red
- B Blue



Made in USA