

# Commercial Emergency Lights

IM



## Dimensions

IM

Height: 6.5"  
Width: 16.0"  
Depth: 4.5"

## Options

Add Suffix to Catalog Number

-P2 Cord & Plug for 120 VAC Input

-Blk Black Finish

The IM Series offers a high-end look for low-budget dollars. Designed to meet demanding architectural requirements, the attractive bevel design and recessed lamp heads complement commercial environments.



Made in USA

## Series Features

- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating
 

120VAC	60 Hz	0.05 Amps
277VAC	60 Hz	0.02 Amps



- HIT Lamps STD Lamp: See Unit Information
- PAR-36 Sealed Beams Opt. PAR-36LED Sealed Beams 5W



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Contemporary Bevel Design
- 20-Gauge Steel Housing
- Fully Recessed Lamp Enclosures
- Bi-Axial Lamp Rotation
- Universal Mount Backplate
- White Powder-Coat Finish
- Red (Power On) and Green (Trickle Charge) LED Indicators
- Test Switch
- UL Listed
- New York City Approved/Calendar #38236

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2IM6S8†	8	18	14	9	7	-	-	-	-	(1) S68
2IM6S10†	8	32	24	16	12	10	8	7	6	(1) S610SL
H2IM6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL
H2IM6S16†	12	36	27	18	14	11	9	8	7	(2) S68

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours. NEC requires 1.5 hours of emergency illumination.

## Ordering Information

LS	2	IM	6	S	10	-8
LS-LED H-Halogen	Lamp Heads on Unit	Series	DC Battery Voltage	Battery Type (S - Sealed)	Battery Amp/Hour	Options