

KXTEU DIE-CAST ALUMINUM EXIT SIGN

ΟΡΤΙΟΝΑΙ

STANDARD

ILLUMINATION

• Ultra bright, energy efficient, long life Red or Green LEDs.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Premium-grade, die-cast aluminum housing (also available in optional black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.

ORDERING INFORMATION


OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



Sample Part Number: KXTEU1RBAEM

Special voltage options	MODEL	No. of FACES		LETTER COLOR		HOUSING COLOR		FACE PANEL		BATTERY		OPTIONS	
available. Check with your Best Lighting	KXTEU	1	Single Face	R	Red	W	White	W	White	(blank)	AC-Only	SDT	Self-Diagnostics ¹
Representative.		2	Double Face	G	Green	В	Black	В	Black	EMn	Battery	2C	Dual Circuit
¹ Available only with EM unit	s.	3	Universal Single/	λ/	emel	CA(Alyminum	A	Aluminum	CON	Backup		Operation ²
² Available only with AC units	S.		Double Face VV	VV .	Cine	9						TP	Tamper-Proof
2												USA	Assembled In USA