LEDCXTEU

ALL LED **EXIT & EMERGENCY** THERMOPLASTIC COMBO

STANDARD



ILLUMINATION

- Long lasting, efficient ultra bright white LED lamp heads.
- 1.0 watt (8 LEDs x 0.125W) per head.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provides optimal center-tocenter spacing.
- Long life, energy efficient Red or Green LED EXIT sign illumination.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 9.6V Long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.

ORDERING INFORMATION

OPTIONS

- RC: Remote capacity of up to 3.0 watts.
- HL: 12-LED heads provide increased center-to-center spacing (1.5W per head).

Your custom

wording > here!


CUSTOM SIGNAGE AVAILABL

- NH: No lamp head attach to the unit enabling it to be used as remote capable exit sign.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- Custom: Signs available with requested "special" wording.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 40°C).
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



Sample Part Number: LEDCXTEU2RW

Special voltage & SALIDA face plate options available. Check with your Best Lighting Representative.	MODEL	No. of FACES		LETTER COLOR		HOUSING COLOR		OPTIONS	
	LEDCXTEU	2 W.	Universal Single/ Double Face	R	Red	W	White	RC	Remote Capacity
				G	Green	В	Black	HL	High Lumen
			emergency	/-li	ghting	.CC	וווע	NH	No Lamp Heads
			child get .	Í				SDT	Self-Diagnostics
								CUSTOM	Custom Wording