

DATE:	COMMENTS:
PROJECT:	

## FEATURES

- Illumination 4 times brighter than UL 924 requirement with super-bright, long-life LEDs that have a 25+ year life expectancy
- Fully self-contained components with captive screws
- Premium long-life, high-temperature fused nickel cadmium battery with above standard UL listed 4-hour run time
- Battery diagnostic system standard – battery status: detects cell failure and issues alert of reduced capacity and the need to replace battery
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power
- Brownout detection ensures emergency operation during periods of low line voltage
- Sealed external momentary test switch and dual diagnostic LED indicator displays AC presence and Hi-Charge status
- Self-Test / Self-Diagnostic monitoring available
- Zero current low-voltage disconnect
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life
- Fine grain brushed aluminum stencil trim standard
- Specialty finish upon request
- 120/277 VAC field-selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering)



## ORDERING INFORMATION LPDC-HD-AC-G-1-BA-BA-MB

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FACE COLOR	6. FRAME COLOR
LPDC-HD	-	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1 Single 2 Double	BA Brushed Aluminum <sup>1</sup> BK Black <sup>2</sup> CC Custom Color WH White <sup>3</sup>	BA Brushed Aluminum BK Black CC Custom Color WH White
7. MOUNTING	8. OPTIONS				
MB Back Mount MTEB Top/End/Back Mount	BLANK = NO OPTION C1 Dual Circuit - 120 VAC (AC Only) C2 Dual Circuit - 277 VAC (AC Only) SD Self-Diagnostics (EM Only) SR Self-Diagnostics + IR Remote Testing Receiver (EM Only) FL Flasher			FLA Flasher/Audible Alarm FA Fire Alarm Interface FAA FA Option w/Audible Alarm (12-24VDC Fire Alarm) LD Damp Location VR 1/8" Vandal Resistant Lens (Includes Tamperproof Screws)	

### ORDERING NOTES

1. Brushed Aluminum Faces Available with Brushed Aluminum, Black and White Frame/Housing
2. Black Face Available With Black Housing
3. White Face Available with Black Housing

### ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wireguard Wall Mount 14" X 10" X 4.5"
- WG 3 = Wireguard Ceiling Mount 14.5" X 6" X 10.5"
- WG 10 = Wireguard End Mount 13.5" X 12" X 16.5"
- TLRT = Infrared Remote Control

## INPUT POWER

- AC models: Red 1.5W; Green 2.3W
- EM models: Red 2.5W; Green 3.0W
- EM w/Remote: Red 3.0W; Green 4.0W

## CONSTRUCTION

- Made from two piece, thick wall, heavy-duty, die-cast aluminum alloy

## LETTERS

- 6.0" high; 0.75" stroke

## ARROWS

- NFPA type, universal field-selectable chevrons

## WEIGHT

- AC: 4.5 lbs
- EM: 5.25 lbs

## TEMPERATURE RATING

- From 32°F to 102°F

## APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA Life Safety Code 101
- NFPA 70- NEC
- OSHA

## WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

## DIMENSIONS

