

DATE:

PROJECT:

COMMENTS:

### FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent, LED, metal halide, or mercury vapor lighting for 60 minutes (must be externally illuminated during normal building occupation)
- PH100 tested and listed per UL924 requirements for use with LED lighting
- 100.0' viewing distance
- Suitable for hazardous locations
- Approved for damp locations
- 25+ year life expectancy
- Maintenance-free
- Universal, field installed chevrons
- Non-electrical
- Fast, easy installation



### ORDERING INFORMATION *PHP100-1-WH-MTEB*

#### 1. SERIES

PHP100

#### 2. FACE COUNT

- 1 Single
- 2 Double

#### 3. FRAME COLOR

WH

WH White

#### 4. MOUNTING

MTEB

MTEB Top/End/Back Mount

#### ACCESSORIES; ORDER SEPARATELY

- WG 2 = Wire guard 14.0" X 10.0" X 4.5"
- WG 3 = Wire guard 14.5" X 6.0" X 10.5"
- WG 10 = Wire guard 13.5" X 12.0" X 16.5"

### SPECIFICATIONS

#### CONSTRUCTION

- Durable ABS panel

#### APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

#### WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

### DIMENSIONS

