

PXL12120F2

- HIGH RATE
LONG LIFE TYPE -




Specifications


Nominal Voltage	12V
Rated Capacity (20 hour rate)	11 Ah
Weight	9.7 lbs. (4.40 kg)
Case Material	Synthetic Resin (ABS)

Dimensions

Length	5.94 inch (151.0mm)
Width	3.86 inch (98.0mm)
Height	3.70 inch (94.0mm)
Total Height	3.98 inch (101.0mm)



Standard Terminal
F2 : AMP Fasten
Type 250



Characteristics

Energy Density	1.56 Watt-hours/cubic inch
Specific Energy	13.6 Watt-hours/pound
Maximum Discharge Current with Standard Terminals	66 A
Maximum Short Duration Discharge Current	165 A (less than 5 sec.)
Vibration Test	No Loss Capacity or Performance (2000 cycles/minute, 0.10 excursion, 2 hours)
Charge Retention (Shelf Life)	% of Nominal Capacity at 77°F (25°C) 1 month 97% 3 month 90% 6 month 80%
Recommended Ambient Temperature Range	Charge : 32°F (0°C) to 104°F (40°C) Discharge : -4°F (-20°C) to 122°F (50°C) Storage : -4°F (-20°C) to 104°F (40°C)
Internal Resistance of Fully Charged Battery	25 Milliohms

Charging

Recommended Charging Methods	CYCLE USE : Maximum Initial Charge Current : 2.75A Charging Voltage : 14.4 ~14.7V Charge Should Be Switched to Float Mode or Disconnected When Current Drops to 110mA
	STANDBY USE (Float) : Maximum Initial Charge Current : 2.75A Charge Voltage : 13.5 ~13.8V

End of Discharge Voltage		Discharge Time										
		10M	15M	30M	1H	2H	3H	4H	5H	8H	10H	20H
10.8V	W	279.08	208.95	121.42	69.01	40.73	29.54	23.79	19.90	13.48	11.28	6.22
	A	22.98	17.02	9.66	5.65	3.34	2.42	1.95	1.64	1.10	0.92	0.53
10.5V	W	292.01	219.12	125.35	71.35	42.12	30.47	24.56	20.52	13.93	11.65	6.44
	A	24.17	18.20	10.24	5.80	3.47	2.49	2.02	1.68	1.14	0.95	0.55
10.2V	W	306.29	229.01	129.26	73.52	43.37	31.39	25.34	21.13	14.37	12.00	6.64
	A	25.26	18.94	10.54	5.97	3.58	2.57	2.08	1.73	1.18	0.98	0.57
9.6V	W	330.20	244.23	137.26	78.18	46.01	33.41	26.90	22.39	15.25	12.75	7.04
	A	27.24	20.14	11.25	6.41	3.81	2.74	2.20	1.83	1.25	1.04	0.60