

Quick™ QLX & QLXN Series

Economical, thermoplastic LED exit signs



Construction

- UV stabilized thermoplastic body
- 6 inch EXIT lettering legend, available in red or green
- Field selectable chevrons
- Exit supplied with 2 faceplates and one backplate

Mounting

- Surface mount
- Canopy included for end or ceiling mount applications
- Universal J-Box mounting

Electronics

- Optional Improved Diagnostics
- 120/277 60Hz
- Sealed maintenance free Nickel-Cadmium battery for self-powered models
- Compatible with Lightalarms Mini Inverters (contact your sales representative for more information)

Power consumption chart

| AC input |
|-------------------------------|
| 120/277VAC, 60Hz maximum 2.5W |

Accessories (Order as a separate item)

| Description | Product code |
|--|--------------|
| Wire guard (wall mount) | WG1-L |
| Wire guard (ceiling mount and end mount) | WG5-L |

Ordering format

| Series | Legend color | Options |
|---------------------------|--------------|--|
| QLX500= AC-Only | RN= Red | Blank= No option |
| QLXN500= Self-powered | GN= Green | -ID= Improved Diagnostics (audible) ¹ |
| Example: QLXN500RN | | -RID= Remote capacity 3.6V-3.6W Improved Diagnostics (audible) ^{1,2} |

¹ Available with red legend only

² Remote capacity for (1) LCARDSQLED, (1) ELF612D/LED or (2) ELF612/LED remote heads only

Finishes

Mist white

Approvals

- UL 924 listed
- Damp location 50°F to 104°F (10°C to 40°C)
- UL 94, 5VA flame rated

Warranty (subject to proper installation and maintenance)

Three-year full warranty

Detailed warranty terms located on **page 197** or online at: www.lightalarms.com



Dimensions

(Dimensions are approximate and subject to change):

