

Series Features



- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating

| | | |
|--------|-------|-----------|
| 120VAC | 60 Hz | 0.20 Amps |
| 277VAC | 60 Hz | 0.20 Amps |



- Optional LED Bulbs 1.5-Watt
- High Intensity Tungsten Lamps, 9-Watt



- Sealed Lead Calcium Battery
- 6 or 12 Volt Operation
- Maintenance Free



- Compact Design
- Injection Molded Polycarbonate Housing
- High Impact, White Finish
- Red (Power On) LED Indicator Light
- Test Switch
- Damp Location
- UL 924 Listed

RC



The RC series features a polycarbonate housing in the BBEM-6 family. The RC is great for applications where remotes or extended battery time is needed.

Dimensions

RC
 Height: 7.5"
 Width: 14.75"
 Depth: 6.75"

Options

- Add Suffix to Catalog Number
- P2 Cord & Plug for 120 VAC Input
 - L LED Heads

Unit Information

| Model Number | Std. Lamp Watt | Watts per Hour | | | | Replacement Battery |
|--------------|----------------|----------------|----|----|----|---------------------|
| | | 1.5 | 2 | 3 | 4 | |
| 2RC6S20 | 9 | 54 | 48 | 32 | 24 | (2) S610SL |
| 2RC12S10 | 9 | 54 | 48 | 32 | 24 | (2) S610SL |

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 48 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

| 2 | RC | 6 | S | 20 |
|--------------------|--------|--------------------|---------------------------|------------------------|
| Lamp Heads on Unit | Series | DC Battery Voltage | Battery Type (S – Sealed) | Battery Type Amp/ Hour |

