

## RCHXL-FE

## Series Features

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC)
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling or Back Mount
- Recessed or Surface Mount Housing
- Clear Acrylic, Edge Lit Panel
- Silk Screen Letters
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Chicago Code



## Dimensions

Width: 24.00"  
Height: 12.00"  
Depth: 6.00"

## Options

Add Suffix to Catalog Number

- 2CKT (2) Independent AC Circuits
- E End Mount (Use Surface Mount – Ceiling as Base Model)
- SS Stainless Steel Trim

For Ceiling Recessed Mount Models Only:

- PA Plenum Construction (for Ceiling Recessed models only)



Made in USA



## Additional Emergency Unit Features

- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery Backup Option
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free
- Test Switch
- LED (Power On) Indicator

\*Longer Illumination Times Available. Consult Factory.

## Specify Arrow Configuration on all Open-Face Signs

Blank = No Arrow

AR = Arrow Right

AL = Arrow Left

DA = Dual Arrow

ARAL = Arrow Right/  
Arrow Left

(Double-Face Only – 1 Arrow per Face)



## Ordering Information

RCHXL-FE	1	W	R	W	C	R	-PA
RCHXL-FE AC Only	# Faces	Trim Color	Letter Color	Background Color	Fixture Type	Mounting Type	Options
ERCHXL-FE Battery Backup	1 2	White* Black BR Brass PM Painted Matte Chrome	Red	White	Ceiling Wall	Recessed Surface	Factory Options