DESCRIPTION

The AtLite New York City-approved Steel LED Combination Exit/ Emergency Rival LED Series is illuminated by a field replicable, high brightness LED strip. Extra capacity for use with remote fixtures is standard as each unit can drive 4 total LED heads. From one to three LED heads can be mounted directly to the unit and the additional capacity can be used to drive remotes up to a total of four LED heads. The emergency lighting heads are aimable, offering exceptional illumination for safe egress. The series exceeds all applicable NEC and NFPA requirements and is UL 924 listed.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

Electrical

- Dual Voltage Input 120/277 VAC, 60Hz
- Solid-state circuitry-no mechanical relay is used
- Output short-circuit and reverse polarity protected
- Transfer with AC line-latching

Battery

 Maintenance-free, long-life NiCd battery

Housing Construction

- Formed 20 gauge steel housing and face plate construction
- Durable powder coat white finish standard; other finishes available
- Easily removed updated directional chevrons
- Variety of electrical and universal J-box mounting knockouts for easy installation
- Low-profile mounting canopy

Code Compliance

 Meets or exceeds all current UL924 requirements, Life Safety Code, NFPA 101, NEC/OSHA and most state and local codes

Remote Capacity

- 2 head combo has an additional 2 heads of remote capacity (RF remote series)
- 3 head combo has an additional 1 head of remote capacity (RF remote series)




ATLITE®




RIVAL LED COMBINATION

Steel Combination LED Emergency and LED Exit Sign
Exit Lighting



RCS183LED

ORDERING INFORMATION



OPTIONS AND ACCESSORIES

OPTIONAL: LED REMOTE HEADS

RFLED401	Single LED Remote Head
RFLED402	Double LED Remote Head