





Project:	
Location:	
Cat.No:	
Type:	
Lamps:	Qty:
Notes:	

Example: SCLRW3

SCLRW3 Combo - Red LED, white housing, universal white exit face, 3-12 Watt tungsten lamp heads

Accessories

WG5 - Wire Guard

Note

For black housing change the "W" to a "B" in above catalog number

codes and standards

- · UL listed to Standard 924
- · NFPA 101 (Life Safety Code)
- · NFPA 70 (National Electric Code)
- New York City Approved (8" letters)
- · UL listed for damp location

construction

- Housing and canopy constructed of 20 gauge steel.
- Field selectable chevrons.
- Housing is finished in a white durable powder coat.
- · Black housing available.

installation

- · Wall mount hardware is included.
- Combos come provided with an extra lamp head for 3 lamp head applications.
 (3rd lamp head to be field installed.

electronics

- Isolated short circuit and voltage protection circuit.
- · Test switch and LED indicator light.
- Low voltage disconnect feature prevents deep battery discharge.
- 24 hour recharge after 90 minute discharge.
- 120/277 VAC, Dual Voltage input.
- Power Consumption: 14.3W max.

LED/lamps

- Exit face illumination is provided by a special high intensity indirect red LED strip.
- Letter brightness and illumination uniformity exceed UL requirements.
- Uniform 8" letter illumination (1" stroke).
- Lamp heads are high impact flame retardant
- Combo lamp heads contain 12 watt tungsten lamps.
- Two or three lamp heads are mounted on top of combo.

battery

- Maintenance free 6V sealed lead acid battery.
- Provides a minimum 90 minutes of emergency illumination while in the emergency mode.

warranty

 Five year warranty on exit. (lamps not included.)



SCL LED die-formed steel exit/unit combo

NYC Approved 8" letters

dimensions



