



SLX-60

ABS Plastic Frame Self Luminous Exit Sign

DATE:

COMMENTS:

PROJECT

FEATURES

- Requires no electricity or external light source
- Maintenance free – no lamps or batteries to replace
- Tamper-proof design
- Easy to install – no wiring required
- Ideal for damp, wet, explosion proof, and extreme temperature applications
- Special wording and pictographs available
- Service life – 10 or 20 year options available



ORDERING INFORMATION *SLX-60-10-1-BK-BA-MTEBP*

1. SERIES

SLX-60

2. SERVICE LIFE

10 10 Years
20 20 Years

3. FACE COUNT

1 Single
2 Double

4. FACE COLOR

BK Black
G Green
R Red

5. FRAME COLOR

BK Black
GY Gray
WH White

6. MOUNTING

MTEBP Universal Mount
MPA 12" Pendant Mount
MPB 24" Pendant Mount
MPC 36" Pendant Mount
MPD 48" Pendant Mount

7. OPTIONS

BLANK = NO OPTION
CW Custom Wording
VR 1/8" Vandal Resistant Lens (Includes Tamperproof Screws)

ACCESSORIES; ORDER SEPARATELY

- WG 5 = Wireguard 15.75" x 14.75" x 6.75"

CONSTRUCTION

- Flame retardant, UV stabilized, injection molded ABS frame

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 ft visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas—a natural hydrogen isotope

WEIGHT

- Single Face: 2.5 lbs
- Double Face: 5 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class 1, 11, and 111 conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website

DIMENSIONS
