SRH

INCANDESCENT INDOOR STEEL REMOTE HEAD



ILLUMINATION

- Long lasting, efficient, wedge base incandescent or bi-pin halogen lamps.
- High performance chrome-plated metallized reflector and glass lens for optimal light distribution.
- Adjustable 6V or 12V lamp heads increase center-tocenter spacing.

ELECTRICAL

 Powered from low voltage power source with low voltage wiring (not provided).

MOUNTING

- Universal mounting adapter plate included. Mounts to single-gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.


HOUSING

Durable 20-gauge steel in white or black finish.

WARRANTY / LISTING

- Five year warranty.
- UL Listed with approved Best Lighting Products.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

DIMENSIONS



FIXTURE COMPATIBILITY CHART

Reference individual unit equipment specification sheets for remote load capacity availability.

MODEL TYPE	6V	12V
NYDXR-50		Χ
RMR-16-65	Χ	
RMR-16-125		Χ
R-5HO	Χ	
R-16-HO	Χ	
DXR-65/610	Χ	
LEDCADXR	Χ	

	l	MODEL TYPE	6V	12V
		TFX-2	Χ	
		NYDXR-27	Χ	
		EZXTE-RC	Χ	
		CXTE-RC	Χ	
		DXR-125/1210		Χ
		CALEDCXTE	X	
1	Ι.	·		

Sample Part Number: SRH-1-12V7.2W

ORDERING INFORMATION

MODEL	No. of HEADS		No. of HEADS COLOR		VOLTAGE		WATTAGE ¹		LAMP TYPE	
SRH1	1	Single Head	(blank)	White	6V	For Use With 6V	5.4W	5.4 Watts ³	(blank)	
	2	Double Head	В	Black		DC Power Source	7.2W	7.2 Watts		Incandescent
					12 V	For Use With 12V DC Power Source	9.0W	9.0 Watts	BPH ²	Bi-Pin Halogen
						Do i ower doured	12.0W	12.0 Watts		

Wattage rating stated per head.

² Available in 12W only.

³ Available in 6V only.