

Job/Location: _____	Job Type: _____
Contractor: _____	Date: _____
Prepared By: _____	



■ **srv - single cube vandal resistant emergency remote**

The **SRV** series features a single polycarbonate cube mounted on a 20 gauge steel back plate. Universal mounting pattern and key hole slots are stamped into the back plate for easy installation. Up to two [2] 35W lamps or up to one [1] 50W lamp.

■ **srvd - double vandal resistant emergency remote**

The **SRVD** series features double **SRV** cubes separated with a 20 gauge steel cabinet. Universal mounting pattern and key hole slots are stamped into the back plate for easy installation. A white powder coat finish is supplied as standard (other colors optional). The operating temperature is from -22°F up to 104°F (-30°C up to 40°C).

■ **srvc - double cube vandal resistant emergency remote**

The **SRVC** features two **SRV** cubes mounted side-by-side to a 20 gauge steel backplate. Universal mounting pattern and key hole slots are stamped into the back plate for easy installation. A white powder coat finish is supplied as standard (other colors optional).

■ **lamp selection**

	6V	12V	24V	120V
Incandescent	5.4, 7.2, 9W	9, 12, 18W	9, 18W	N/A
Halogen	12, 20W	12, 20W	12, 20W	N/A
MR16	6, 10W	10, 12, 20, 35, 50W	12, 20, 35, 50W	N/A
MR16-GU10	N/A	N/A	N/A	35, 50W
MR16 LED	5, 7W	2, 5, 7W	5, 7W	N/A

■ **ordering information**

Series	Lamps	Voltage / Wattage	Option
VR	1 (One)	See lamp selection	TPS (Tamper proof screws)
	2 (Two)		CC (Custom color)
VRD	2 (One per cube)		TPS (Tamper proof screws)
	4 (Two per cube)		CC (Custom color)
VRC	2 (One per cube)		TPS (Tamper proof screws)
			CC (Custom color)

Note: Maximum capacity per cube is 70W