



LED Classic Filament T-Lamps

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

The filament style LED T-lamps from TCP provide beauty and versatility as traditional T-lamps with the savings of LED. Exclusive LED technology provides unmatched longevity and perfect 5-100% dimming.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Accent Lighting
- Decorative Lighting
- General Lighting

FEATURES	BENEFITS
Energy efficient	Up to 85% less energy than halogen lamps
Very low heat generation	Minimizes replacement and maintenance costs
Long life	15,000 hours rated life
UL approved for damp and enclosed locations	Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors
Appearance	Unique filament LED configuration provides a uniform color output
ANSI construction compliant	Fits most general applications

★ Smooth, Uniform Dimming from 5 - 100% ★

SPECIFICATIONS

Color Temperature options..... 2200K, 2400K, 2700K, 3000K, 4000K, 5000K
Input Line Voltage 120 VAC
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 15,000 hours
Minimum Starting Temp -30°C
Maximum Operating Temp..... 40°C
CRI..... >80
Base E12/E26



RoHS
COMPLIANT

3 YEAR
WARRANTY

*Based on 12 hours use per day



T6 25W
E12 bases

T10 25W/40W
E26 bases

T25 25W
E12 base

T30 60W
E26 base

LED
we know light.™

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com



LED CLASSIC FILAMENT T-LAMPS

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

ITEM #	DESCRIPTION	LED WATTS	INCAND. WATTS	LUMENS	FILAMENTS	CRI	COLOR TEMP	GLASS TYPE	MOL (inches)	DIA (inches)	BASE
--------	-------------	--------------	------------------	--------	-----------	-----	---------------	---------------	-----------------	-----------------	------

T6



25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour

FT0603D2522E12SB	T6 25W 2200K E12 SANDBLAST	3.0	25	200	2	>80	2200K	SandBlast	3.3	0.8	E12
FT0603D2524E12SB	T6 25W 2400K E12 SANDBLAST	3.0	25	200	2	>80	2400K	SandBlast	3.3	0.8	E12
FT0603D2527E12C	T6 25W 2700K E12 CLEAR	3.0	25	250	2	>80	2700K	Clear	3.3	0.8	E12
FT0603D2527E12W	T6 25W 2700K E12 FROST	3.0	25	250	2	>80	2700K	Frosted	3.3	0.8	E12

T10



25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour

FT1005D2524SB	T10 25W 2400K E26 SANDBLAST	3.5	25	250	2	>80	2400K	SandBlast	5.4	1.2	E26
FT1005D2527EC	T10 25W 2700K E26 CLEAR	3.5	25	250	2	>80	2700K	Clear	5.4	1.2	E26
FT1005D2527EW	T10 25W 2700K E26 FROST	3.5	25	250	2	>80	2700K	Frosted	5.4	1.2	E26
FT1005D2550EC	T10 25W 5000K E26 CLEAR	3.5	25	250	2	>80	5000K	Clear	5.4	1.2	E26
FT1005D2550EW	T10 25W 5000K E26 FROST	3.5	25	250	2	>80	5000K	Frosted	5.4	1.2	E26
FT1007D2522SB	T10 25W 2200K E26 SANDBLAST	3.0	25	250	1	>80	2200K	SandBlast	7.0	1.2	E26
FT1007D2522SB	T10 25W 2200K E26 SANDBLAST	3.0	25	250	1	>80	2200K	SandBlast	7.0	1.2	E26
FT1007D2524SB	T10 25W 2400K E26 SANDBLAST	3.0	25	250	1	>80	2400K	SandBlast	7.0	1.2	E26



40 Watt Replacements • Dimmable • E26 Base • 15,000 Hour

FT1005D4027EC	T10 40W 2700K E26 CLEAR	5.0	40	450	4	>80	2700K	Clear	5.4	1.2	E26
FT1005D4027EW	T10 40W 2700K E26 FROST	5.0	40	450	4	>80	2700K	Frosted	5.4	1.2	E26
FT1005D4030EW	T10 40W 3000K E26 FROST	5.0	40	450	4	>80	3000K	Frosted	5.4	1.2	E26
FT1005D4040EW	T10 40W 4000K E26 FROST	5.0	40	450	4	>80	4000K	Frosted	5.4	1.2	E26
FT1005D4050EC	T10 40W 5000K E26 CLEAR	5.0	40	450	4	>80	5000K	Clear	5.4	1.2	E26
FT1005D4050EW	T10 40W 5000K E26 FROST	5.0	40	450	4	>80	5000K	Frosted	5.4	1.2	E26

T25



25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour

FT2503D2527E12C	T25 25W 2700K E12 CLEAR	3.5	25	250	4	>80	2700K	Clear	3.6	1.0	E12
-----------------	-------------------------	-----	----	-----	---	-----	-------	-------	-----	-----	-----

T30



60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour

FT3014D6022SB	T30 60W 2200K E26 SANDBLAST	8.0	60	800	1	>80	2200K	SandBlast	14.0	1.2	E26
FT3014D6024SB	T30 60W 2400K E26 SANDBLAST	8.0	60	800	1	>80	2400K	SandBlast	14.0	1.2	E26
FT3014D6027SB	T30 60W 2700K E26 SANDBLAST	8.0	60	800	1	>80	2700K	SandBlast	14.0	1.2	E26
FT3014D6027EC	T30 60W 2700K E26 CLEAR	8.0	60	800	1	>80	2700K	Clear	14.0	1.2	E26



RoHS
COMPLIANT

3 YEAR
WARRANTY
*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP JUL 2019 / WF157104