

## Series Features



- Choice of Light Source  
LED (Indirect View) 25+ Years
- LED Models have Double LED Strips for Increased Illumination



- Triangular Shape
- Two- or Three-Face Signs Available
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Back Mount (Two-Face Signs)
- Ceiling or Pendant Mount (Three-Face Signs)
- Directional Chevron Snapouts
- Meets or Exceeds UL 924

## Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- AC Lockout (Line Latching)



- Sealed Lead Calcium Battery  
5-Year Warranty OR
- Sealed Nickel Cadmium Battery  
10-Year Warranty
- Maintenance-Free



- Test Switch
- Red (Power On & Charge) Indicator

## Unit Information

Series	Light Source	Standard Voltage	Max. Input Watts (120VAC)	Max. Input Watts (277VAC)	Replacement Battery
AC Only					
TRXL	LED (Indirect)	120/277V	3.5W	3.5W	N/A
Emergency					
ETRXL	LED (Indirect)	120/277V	3.5W	3.5W	N71

## Ordering Information

ETRXL	1	R	W	W	-QC
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
TRXL-AC/LED ETRXL-EM/LED	2 3	Red Green	White Black	White Black	Factory Options

## TRX



### Options

Add Suffix to Catalog Number

-277 277VAC Input

-2CKT (2) Independent AC Circuits


### Accessories

Order Separately

P12W 12" Pendant Kit, White\*

P12B 12" Pendant Kit, Black\*

\*Pendant Kits from 12" to 84" Available



Made in USA



UL 924 LISTED