

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- 5 Year Warranty



Commercial Recessed Downlight



Specification Data

Model No.	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR4D/9T/14W-10V	6 / 9 / 14	550 / 770 / 1100	3000K, 3500K, 4000K selectable	90 / 85 / 78	120-277	90	0.9	Dia. 5.71" x Height 3.70"

Ordering Information

Sample model: VEKR4D/9T/14W-10V

VEKR	4D	9T	14W	10V
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>90 T: three CCT adjustable	Wattage 14W Max.	0-10V dimming



User Manual [Recessed Light Installation Guide](#)

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- 5 Year Warranty



Commercial Recessed Downlight



Specification Data

Model No.	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR6D/9T/21W-10V	8.5 / 13.5 / 21	770 / 1100 / 1650	3000K, 3500K, 4000K selectable	90 / 81 / 78	120-277	90	0.9	Dia. 8.27" x Height 4.25"

Ordering Information

Sample model: VEKR4D/9T/14W-10V

VEKR	4D	9T	14W	10V
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>90 T: three CCT adjustable	Wattage 14W Max.	0-10V dimming



User Manual

[Recessed Light Installation Guide](#)

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Works in cold temperature applications
- 5 Year Warranty



Commercial Recessed Downlight



Specification Data

Model No.	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Dimension
VEKR8D/9T/27W-10V	12 / 19 / 27	1100 / 1650 / 2200	3000K, 3500K, 4000K selectable	90 / 85 / 80	120-277	90	0.9	Dia. 10.24" x Height 4.57"

Ordering Information

Sample model: VEKR4D/9T/14W-10V

VEKR	4D	9T	14W	10V
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>90 T: three CCT adjustable	Wattage 14W Max.	0-10V dimming



User Manual

[Recessed Light Installation Guide](#)