

# Steel-Diffused LED Exits

XFL



XFL/EXFL

## Dimensions

### STANDARD

Height: 7.5"  
Width: 12.3"  
Depth: 2.0"

### NEW YORK CITY APPROVED

Height: 11.0"  
Width: 14.5"  
Depth: 2.3"

## Options

Add Suffix to Catalog Number

- 6 (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12 (2) 12VDC Lamps for AC/12VDC Remote Operation
- DMP Damp Location Listing (Damp Label)
- DS Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation
- HI High-Intensity LEDs
- NY New York City Approved with 8" Letters
- REC Recessed Housing (Single-Face Only)
- TP Tamper-Proof Screws
- U Universal Face (Additional Backplate – Double-Face Signs Only)

## Accessories







Order Separately

- 63 Wire Guard (for Single-Face Back Mount Only)
  - P12W 12" Pendant Kit, White\*
  - P12B 12" Pendant Kit, Black\*
- \*Pendant Kits from 12" to 84" Available
- VDS Vandal-Deterrent Shield (for Single-Face Back Mount Only)














Made in USA

## Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC)  
Standard 1.7 Watts  
DS Option 3.5 Watts
-  • Light-Emitting Diodes – 25+ Year Life
-  • Illuminates with Uniform Color and Brightness
-  • Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
-  • Directional Chevron Snapouts
- 20-Gauge Steel Housing
- White Powder-Coat Finish
- Easy Installation
- UL Listed

## Additional Emergency Unit Features

-  • Integrated Solid State System
-  • Constant Current, Controlled Automatic Charger Circuit
-  • Low-Voltage Battery Cutoff
-  • Brownout Sensitivity
-  • Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery
-  • 5-Year Shelf Life
-  • 10-Year Battery Warranty
-  • Maintenance-Free
-  • 3+ Hours Illumination in Emergency Mode\*
-  • Test Switch
-  • LED (Power On) Indicator

\*Longer Illumination Times Available. Consult Factory.

## Ordering Information

EXFL	1	R	W	W	-DS
XFL-AC Only EXFL – Emer.	# Faces 1 2	Letter Color Red Green	Stencil Color White Black PM Painted Matte Chrome	Housing Color White* Black PM Painted Matte Chrome	Option Factory Options