

The XKL is a traditional thermoplastic Exit sign. Universal faces and field selectable chevrons are included. Available with a 3.6V NiCad Battery. Also available with Remote Capability and Self-Diagnostics.

FEATURES

- 120/277 VAC Operation
- Maximum Input Rating
- (120 or 277VAC) 1.7 Watts Standard
- Light-Emitting Diodes –25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy Kit Included
- Universal Stencil
- Directional Chevron Snapouts
- White Finish Standard
- Easy Installation
- UL Listed and CEC Registered
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location
- Additional Emergency Unit Features
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Initial Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery
- Test Switch
- LED (Power On) Indicator

WARRANTY

5 Year Warranty

Dimensions

XKL / EXKL

Height: 8.75"
 Width: 12.25"
 Depth: 2.5"



XKL

The XKL Offers a fast and easy installation in an economical package

Options:

- * **SD** – Self Diagnostic
- * **RC** – Remote Capable (Additional 3.4W per 90 Minutes)
- * **SALIDA**
- * **Ask about Custom Signage**



| Series | Universal Faces | Letter Color | Housing Finish | Stencil Finish | Universal | Options |
|-----------------------|-----------------|--------------|----------------|----------------|-----------|------------------------|
| XKL = AC Only | 2 | R = Red | W = White | W = White | U | -SD = Self Diagnostics |
| EXKL = Battery Backup | | G = Green | B = Black | B = Black | | |
| | | | | | | |
| | | | | | | |