



# XRH

XRH Steel MR16 or LED Remote Head

|          |           |
|----------|-----------|
| DATE:    | COMMENTS: |
| PROJECT: |           |

## FEATURES

- Rotary locking collar securely locks the lens and reflector assembly into place
- Innovative design allows for quick and easy relamping
- Designed to fit most standard junction boxes
- Swivel lock secures adjustable head in place
- Surface mount on wall or ceiling



## ORDERING INFORMATION *XRH-BK-1-L65*

| 1. SERIES | 2. HOUSING COLOR     | 3. HEAD COUNT                              | 4. LAMP SOURCE  |
|-----------|----------------------|--|---|
| XRH       | -                    | -  | -   |
|           | BK Black<br>WH White | 1 One Lamp<br>2 Two Lamps<br>3 Three Lamps | See Lamp Chart for Part #<br>Example: LED 6V 5W = "L65" |

### ACCESSORIES; ORDER SEPARATELY

- WG 1 = Wireguard 17.0" X 17.0" X 17.0"
- WG 4 = Wireguard 6.0" X 8.0" X 6.0"

## SPECIFICATIONS

### CONSTRUCTION

- High grade steel
- Glass lens will not yellow over time

### APPROVALS

- UL924
- NFPA 101 Life Safety Code
- NFPA 70 - NEC
- OSHA

### WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

## LAMP CHARTS

| L - LED |     |      |      |
|---------|-----|------|------|
|         | 6V  | 12V  | 24V  |
| 2W      |     | L122 |      |
| 5W      | L65 | L125 | L245 |
| 7W      | L67 | L127 | L247 |

| M - MR16 |      |       |       |
|----------|------|-------|-------|
|          | 6V   | 12V   | 24V   |
| 6W       | M66  |       |       |
| 10W      | M610 | M1210 |       |
| 12W      |      | M1212 | M2412 |
| 20W      |      | M1220 | M2420 |
| 35W      |      | M1235 | M2435 |
| 50W      |      | M1250 | M2450 |