

Surface Mount Edge-lit Exits

Exit Signs

EDG

LED

Intended Use

Suitable for applications requiring attractive edge-lit exit signage, universal installation and low energy consumption.

Features

Extruded brushed aluminum finish lamp housing.

Clear thermoplastic panels with precision outline engraved letters measuring 6" high with 3/4" stroke.

Mirrored separator panel to simulate clear background for double face signs. Clear panel for single face signs.

Expected LED life over 25 years.

Low energy consumption – less than 5 watts for 120V red AC only; and battery back-up.

Universal (top, end or back) mounting. Double face available with top or end mounting only (canopy provided).

Universal directional indicators. Field selected and attached.

Listings – UL listed.

NEW



Example: **EDG 1 R 120/277 EL N**

Ordering Information

Family	Housing color	Number of faces	Letter color	Input voltage	Operation
EDG Surface Mount LED edge-lit	(blank) Brushed aluminum	1 Single 2 Double	R Red G Green	120/277 Dual voltage	(blank) Standard non-emergency EL N Nickel-cadmium battery

Electrical Specifications			
Primary Circuit			
Type	Supply voltage	Input watts	Max. amps
Red LED, AC only	120 277	3 3	0.2 0.1
Green LED, AC only	120 277	4 6	0.3 0.2
Red LED, emergency	120 277	5 5	0.4 0.2
Green LED, emergency	120 277	6 6	0.5 0.2

Dimensions are shown in **inches (millimeters)** unless otherwise noted. Shipping weight 4lbs. (1.81 kgs.)

